ELMARK HOLDING SE

CATALOGUE Q4 2021

7 YEARS WARRANTY

ELMARK®

The Brand of Electricity

ACOUSTIC LED RINGS
LUMINAIRES
PAGE 892

LED RINGS
LUMINAIRES
PAGE 893

LED PROFILES S48
LUMINAIRES
PAGE 894

RAINBOW LED SMD
LUMINAIRES
PAGE 901

LENA-V BM/
LUMINAIRES
PAGE 906

XL101
EMERGENCY LIGHTS
PAGE 918

XL3114
EMERGENCY LIGHTS
PAGE 920

EMERGENCY DRIVER
EMERGENCY LIGHTS
PAGE 921

TRITON
BATHROOM
PAGE 934

DORIA
BATHROOM
PAGE 937

LED PANEL ROUND IP44
BATHROOM
PAGE 939

WATERPROOF LED PANEL
BATHROOM
PAGE 941

ELR627
BATHROOM
PAGE 943

OUTDOOR LIGHTING

JOSH
GARDEN
PAGE 947

ERIK
GARDEN
PAGE 950

SCOTT
GARDEN
PAGE 957

GOLIA
GARDEN
PAGE 962

ANNA
GARDEN
PAGE 964

GLOBE 250
GARDEN
PAGE 966

GRF506 LED
GARDEN
PAGE 971

GABRI
GARDEN
PAGE 973

ST92
GARDEN
PAGE 974

CARLO DECO
GARDEN
PAGE 977

CARLO
GARDEN
PAGE 978

SAURO
GARDEN
PAGE 980

PMMA OPAL
GARDEN
PAGE 985

NINA 150
GARDEN
PAGE 987

LED WALL FIXTURES
GARDEN
PAGE 988

LETI 100GR
GARDEN
PAGE 990

LORENZA 190
GARDEN
PAGE 996

WALL LAMP
GARDEN
PAGE 1000

STUCCHI
GARDEN
PAGE 1003

BRICE
GARDEN
PAGE 1007

LED BULKHEAD LAMP
GARDEN
PAGE 1008

GRF9617 LED
GARDEN
PAGE 1010

LIVIA 160
FACADE AND GROUND
PAGE 1015

GRF313
FACADE AND GROUND
PAGE 1021

GRF326
FACADE AND GROUND
PAGE 1022

SOLAR LED WALL LIGHTS
FACADE AND GROUND
PAGE 1028

SOLAR FIXTURE & SENSOR
FACADE AND GROUND
PAGE 1029

GRF318
FACADE AND GROUND
PAGE 1035

SOLAR TORCH LIGHT
FACADE AND GROUND
PAGE 1038

SOLAR GROUND LIGHT
FACADE AND GROUND
PAGE 1039

SOLAR WALL
FACADE AND GROUND
PAGE 1045

ALDO
FACADE AND GROUND
PAGE 1050

CECI
FACADE AND GROUND
PAGE 1051

WADE FIXTURE IP65
LUMINAIRES
PAGE 1055

BELLA SMD2835
LUMINAIRES
PAGE 1057

BELLA LED T8
LUMINAIRES
PAGE 1059

WALL LAMP GRF 312
FLOODLIGHTS
PAGE 1063

HELIOS SMD
FLOODLIGHTS
PAGE 1064

STADIUM FLOOD LIGHTS
FLOODLIGHTS
PAGE 1071

SIRIUS SMD
FLOODLIGHTS
PAGE 1072

LED WORK FLOODLIGHTS
FLOODLIGHTS
PAGE 1074

BERLIN SMD
ROAD LIGHTS
PAGE 1077

MADRID SMD
ROAD LIGHTS
PAGE 1078

SOLAR LED
ROAD LIGHTS
PAGE 1082

FESTA SMD
HIGH BAYS
PAGE 1085

VIENA SMD
HIGH BAYS
PAGE 1086

LAMPS AND COMPONENTS

LED VINTAGE LAMP
LAMPS
PAGE 1095

LED VINTAGE LAMP
LAMPS
PAGE 1097

LED VINTAGE LAMP
LAMPS
PAGE 1099

ELMARK
www.elmarkholding.eu

JOSH
96402WD/BK

JOSH
96403P/BK

JOSH
96404MF/BK

JOSH
96405MF/BK

IP44

JOSH

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96402WD/BK	C	Wall lantern	Matt black	185	240	450	1 x E27	1/6	A++→E
96403P/BK	C	Hanging lantern	Matt black	185	-	290	1 x E27	1/6	A++→E
96404MF/BK	C	Lantern floor post	Matt black	185	-	460	1 x E27	1/6	A++→E
96405MF/BK	F	Lantern floor post*	Matt black	185	-	2000	1 x E27	1/20	A++→E

SP60 METAL POLE
Colour: black
Size (mm):
Diameter 60 x Base Ø 145
Product category: G
Height: 600 - **93SP60BL**
Height: 800 - **93SP80BL**
Height: 1000 - **93SP100BL**
Height: 1200 - **93SP120BL**

Body: Aluminium with glass

*Until supply last

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

JOSH
96402WD/AB

JOSH
96403P/AB

JOSH
96404MF/AB

JOSH
96405MF/AB

IP44

JOSH

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96402WD/AB	C	Wall lantern	Antique brass	185	240	450	1 x E27	1/6	A++→E
96403P/AB	C	Hanging lantern	Antique brass	185	-	290	1 x E27	1/6	A++→E
96404MF/AB	C	Lantern floor post	Antique brass	185	-	460	1 x E27	1/6	A++→E
96405MF/AB	F	Lantern floor post*	Antique brass	185	-	2000	1 x E27	1/20	A++→E

SP60 METAL POLE
Colour: black
Size (mm):
Diameter 60 x Base Ø 145
Product category: G
Height: 600 - **93SP60BL**
Height: 800 - **93SP80BL**
Height: 1000 - **93SP100BL**
Height: 1200 - **93SP120BL**

Body: Aluminium with glass

*Until supply last

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ALEK
96301WD/BK

ALEK
96301WU/BK

ALEK
96305F/BK

ALEK
96303P/BK

ALEK
96304MF/BK

IP44

ALEK

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96301WD/BK	C	Wall lantern	Matt black	150	175	295	1 x E27	1/6	A++→E
96301WU/BK	C	Wall lantern	Matt black	150	175	365	1 x E27	1/6	A++→E
96303P/BK	C	Hanging lantern	Matt black	150	150	230	1 x E27	1/6	A++→E
96304MF/BK	C	Lantern floor post	Matt black	150	150	370	1 x E27	1/6	A++→E
96305F/BK	C	Lantern floor post	Matt black	150	150	830	1 x E27	1/6	A++→E

Body: Aluminium with glass

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ALEK
96301WD/BRB

ALEK
96301WU/BRB

ALEK
96305F/BRB

ALEK
96303P/BRB

ALEK
96304MF/BR

IP44

ALEK

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96301WD/BRB	C	Wall lantern	Antique copper	150	175	295	1 x E27	1/6	A++→E
96301WU/BRB	C	Wall lantern	Antique copper	150	175	365	1 x E27	1/6	A++→E
96303P/BRB	C	Hanging lantern	Antique copper	150	150	230	1 x E27	1/6	A++→E
96304MF/BRB	C	Lantern floor post	Antique copper	150	150	370	1 x E27	1/6	A++→E
96305F/BRB	C	Lantern floor post	Antique copper	150	150	830	1 x E27	1/6	A++→E

Body: Aluminium with glass

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ERIK
96101WU/BK

ERIK
96102WD/BK

ERIK
96105F/BK

ERIK
96103P/BK

ERIK
96104MF/BK

IP44

ERIK

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96101WU/BK	C	Wall lantern	Matt black	155	170	325	1 x E27	1/6	A++→E
96102WD/BK	C	Wall lantern	Matt black	155	170	285	1 x E27	1/6	A++→E
96103P/BK	C	Hanging lantern	Matt black	155	-	300	1 x E27	1/6	A++→E
96104MF/BK	C	Lantern floor post	Matt black	155	-	370	1 x E27	1/6	A++→E
96105F/BK	C	Lantern floor post	Matt black	155	-	775	1 x E27	1/6	A++→E

Body: Aluminium with glass

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ERIK
96101WU/AB

ERIK
96102WD/AB

ERIK
96105F/AB

ERIK
96103P/AB

ERIK
96104MF/AB

IP44

ERIK

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96101WU/AB	C	Wall lantern	Antique brass	155	170	325	1 x E27	1/6	A++→E
96102WD/AB	C	Wall lantern	Antique brass	155	170	285	1 x E27	1/6	A++→E
96103P/AB	C	Hanging lantern	Antique brass	155	-	300	1 x E27	1/6	A++→E
96104MF/AB	C	Lantern floor post	Antique brass	155	-	370	1 x E27	1/6	A++→E
96105F/AB	C	Lantern floor post	Antique brass	155	-	775	1 x E27	1/6	A++→E

Body: Aluminium with glass

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

NICK
96501WU/BK

NICK
96504MF/BK

NICK
96503P/BK

NICK
96505F/BK

IP44

NICK

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96501WU/BK	C	Wall lantern	Matt black	210	175	230	1 x E27	1/12	A++→E
96503P/BK	C	Hanging lantern	Matt black	175	175	220	1 x E27	1/12	A++→E
96504MF/BK	C	Lantern floor post	Matt black	175	175	240	1 x E27	1/12	A++→E
96505F/BK	C	Lantern floor post	Matt black	175	175	720	1 x E27	1/6	A++→E

Body: Aluminium with PVC

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

NICK
96501WU/AB

NICK
96504MF/AB

NICK
96503P/AB

NICK
96505F/AB

IP44

NICK

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96501WU/AB	C	Wall lantern	Antique brass	210	175	230	1 x E27	1/12	A++→E
96503P/AB	C	Hanging lantern	Antique brass	175	175	220	1 x E27	1/12	A++→E
96504MF/AB	C	Lantern floor post	Antique brass	175	175	240	1 x E27	1/12	A++→E
96505F/AB	C	Lantern floor post	Antique brass	175	175	720	1 x E27	1/6	A++→E

Body: Aluminium with PVC

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

PAUL
96511WU/BL

PAUL
96511P/BL

PAUL
96511MF/BL

IP44

PAUL

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96511WU/BL	C	Wall lantern	Black	190	377	230	1xE27	1/6	A++→E
96511MF/BL	C	Standing lantern	Black	100	426	100	1xE27	1/6	A++→E
96511P/BL	C	Hanging lantern	Black	190	836	190	1xE27	1/6	A++→E

Material: UV resistant PP+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS COMPLIANT | 2+1 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

PAUL
96511F/BL

PAUL
96511F2/BL

IP44

PAUL

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96511F/BL	C	Standing lantern	Black	190	1231	190	1xE27	1/6	A++→E
96511F2/BL	C	Standing lantern	Black	600	2174	190	2xE27	1/6	A++→E

Material: UV resistant PP+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS COMPLIANT | 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

KEVIN
96514WU/BL

KEVIN
96514MF/BL

KEVIN
96514P/BL

KEVIN
96514F/BL

IP44

KEVIN

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96514WU/BL	C	Wall lantern	Black	197	350	150	1xE27	1/6	A++→E
96514MF/BL	C	Standing lantern	Black	150	415	150	1xE27	1/6	A++→E
96514P/BL	C	Hanging lantern	Black	150	825	150	1xE27	1/6	A++→E
96514F/BL	C	Standing lantern	Black	197	1200	197	1xE27	1/6	A++→E

Material: UV resistant PP+ Glass | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS COMPLIANT | F | CE | 2+1 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

CARL
96512WD/BL

SCOTT
96513WD/BL

IP44

CARL / SCOTT

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96512WD/BL	C	Wall lantern	Black	170	275	223	1xE27	1/6	A++→E
96513WD/BL	C	Wall lantern	Black	170	310	223	1xE27	1/6	A++→E

Material: UV resistant PP+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

JAMES
96515WU/BL

JAMES
96515P/BL

JAMES
96515F/BL

JAMES
96515MF/BL

IP44

JAMES

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96515WU/BL	C	Wall lantern	Black	165	466	232,5	1xE27	1/6	A++→E
96515MF/BL	C	Standing lantern	Black	165	529	165	1xE27	1/6	A++→E
96515P/BL	C	Hanging lantern	Black	165	940	165	1xE27	1/6	A++→E
96515F/BL	C	Standing lantern	Black	165	1335	165	1xE27	1/6	A++→E

Material: UV resistant PP+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS COMPLIANT | 2+1 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

STEVEN
96516WU/BL

STEVEN
96516P/BL

STEVEN
96516MF/BL

IP44

STEVEN

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96516WU/BL	C	Wall lantern	Black	176	411	238	1xE27	1/6	A++→E
96516MF/BL	C	Standing lantern	Black	176	476	176	1xE27	1/6	A++→E
96516P/BL	C	Hanging lantern	Black	176	882	176	1xE27	1/6	A++→E

Material: UV resistant PP+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS COMPLIANT | 2+1 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MATTHEW
96517WD/BL

ROGER
96518WD/BL

JEREMY
96519WD/BL

IP44

MATTHEW / ROGER / JEREMY

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96517WD/BL	C	Wall lantern	Black	181	250	232	1xE27	1/6	A++→E
96518WD/BL	C	Wall lantern	Black	110	190	150	1xE27	1/20	A++→E
96519WD/BL	C	Wall lantern	Black	252	452	342,5	1xE27	1/4	A++→E

Material: UV resistant PP+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | F | CE | 2+1 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MARK
96201WU/BRB

MARK
96201WU/BK

IP44

UNTIL SUPPLY LAST

MARK

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96201WU/BRB	F	Wall lantern	Antique copper	200	230	420	1 x E27	1/6	A++→E
96201WU/BK	F	Wall lantern	Matt black	200	230	420	1 x E27	1/6	A++→E

Body: Aluminium with glass | **Lamps not included**

~230V | 50/60 Hz | E27 | 1,5mm² | IP 44 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

IESSE
96IESSEWL/BL

GOLIA
96GOLIAP/BL

GOLIA
96GOLIAWL/BL

GOLIA
96GOLIAMF/BL

IP55 **Resin**

MEDIUM SIZE GOLIA/ IESSE

Catalogue number	Product category	Description	Colour	Width (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GOLIAWL/BL	C	Wall lantern	Black	300	450	1xE27	1/12	A++→C
96GOLIAP/BL	C	Hanging lantern	Black	230	800	1xE27	1/12	A++→C
96GOLIAMF/BL	C	Lantern floor post	Black	230	470	1xE27	1/12	A++→C
96IESSEWL/BL	C	Wall half lantern	Black	220	350	1xE27	1/16	A++→C

Lantern body: Resin with clear glass| UV resistant | Lamp not included

Recommended bulbs:

99LED588 LED PEAR A60 12W 4000K | **99LED587** LED PEAR A60 12W 2700K | **99LED821** LED PEAR A60 12W 6400K

99LED773D LED Vintage 8W 2700K

~230V | 50/60 Hz | E27 | RoHS | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.



GOLIA
96GOLIAGG/BL

GOLIA
96GOLIAMG/BL

LED NEUTRAL WHITE 4000K | IP55 | Resin

GOLIA

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Width/ Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96GOLIAMG/BL	C	8	800	4000	Black	230	1100	1	A+ A++→A
96GOLIAGG/BL	C	8	800	4000	Black	230	2110	1	A+ A++→A

Body: Resin with clear glass | UV resistant | **Lampholder:** E27 | **Lamp included**

~230V | 50/60 Hz | E27 | RoHS COMPLIANT | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

ANNA
96120WU/BL

ANNA
96120MF/BL

ANNA
96120P/BL

IP55 **Resin**

SMALL SIZES GARDEN LANTERN ANNA

Catalogue number	Product category	Model	Lamp included	Colour	Width (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96120WU/BL	C	Wall lantern- UP	no	black	275	450	E27	1/18	A++→C
96120P/BL	C	Wall lantern- Hanging	no	black	220	800	E27	1/18	A++→C
96120MF/BL	C	Lantern floor post	no	black	130	385	E27	1/18	A++→C

Lantern body: Resin with glass | UV resistant | Lamp not included

Post lantern body: steel+resin | Anticorrosion | UV-rays stabilized| Not affected by chenical fertilizes

Recommended bulbs:
99LED588 LED PEAR A60 12W 4000K | **99LED587** LED PEAR A60 12W 2700K | **99LED821** LED PEAR A60 12W 6400K
99LED773D LED Vintage 8W 2700K

~230V | 50/60 Hz | E27 | RoHS | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

ANNA 2x6W
96120GB2L/BL

ANNA 6W
96120F/BL

LED NEUTRAL WHITE 4000K **IP55** **Resin**

SMALL SIZES GARDEN LANTERN ANNA

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Width/ Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96120F/BL	C	6	800	4000	Black	220	1100	1	A+ A++→A
96120GB2L/BL	C	2x6	1600	4000	Black	610	2090	1	A+ A++→A

Body: Resin with clear glass | UV resistant | **Lampholder:** E27 | Lamp included

~230V 50/60 Hz E27 RoHS CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

GLOBE 250
96G250WL/BL

GLOBE 250
96G250P/BL

GLOBE 250
96G250MF/BL

IP55 **Resin**

GLOBE 250

Catalogue number	Product category	Description	Colour	Width/ Diameter (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96G250WL/BL	C	Wall lamp	Black	300	360	1xE27	1/36	A++→C
96G250MF/BL	C	Floor lamp	Black	250	350	1xE27	1/36	A++→C
96G250P/BL	C	Hanging lamp	Black	250	700	1xE27	1/36	A++→C

Lantern body: Resin with clear glass| UV resistant | Lamp not included

Recommended bulbs:

99LED588 LED PEAR A60 12W 4000K | **99LED587** LED PEAR A60 12W 2700K | **99LED821** LED PEAR A60 12W 6400K

99LED773D LED Vintage 8W 2700K

~230V | 50/60 Hz | E27 | RoHS | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

GLOBE 250
96G250M/BL

GLOBE 250
96G250GB2L/BL

LED NEUTRAL WHITE 4000K | IP55 | Resin

GLOBE 250

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Width/ Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96G250M/BL	C	6	800	4000	Black	250	1000	1	A+ A++→A
96G250GB2L/BL	C	2x6	1600	4000	Black	250	2050	1	A+ A++→A

Body: Resin with clear glass| UV resistant | Lampholder: E27 | Lamp included

~230V | 50/60 Hz | E27 | RoHS COMPLIANT | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

GRF157 LED
96LEDW157

GRF157 LED
96LEDP15780

GRF507 LED
96LEDW507

LED NEUTRAL WHITE 4000K **IP54**

UNTIL SUPPLY LAST

GRF157 LED / GRF507 LED

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96LEDW157	F	10	800	4000	dark gray	250	90	80	1/9	A++→A
96LEDP15780	F	10	800	4000	dark gray	800		100	1/9	A++→A
96LEDW507	F	10	800	4000	graphite black	160	112	170	1/12	A++→A

Material: Alu+PC | **Chip:** 8 pcs Osram SMD3030

~230V | 50/60 Hz | SMD 2835 | 30000h | >20000 | IP 54 | Ra>80 | Hg | RoHS | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

GRF206 LED
96LEDW206
96LEDW206WW

GRF206 LED
96LEDP20678
96LEDP20678WW

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP54

GRF206 LED

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96LEDW206	C	10	800	4000	graphite black	164	80	263	1/16	A++→A
96LEDP20678	C	10	800	4000	graphite black	154	110	780	1/6	A++→A
96LEDW206WW	C	10	800	3000	graphite black	164	80	263	1/16	A++→A
96LEDP20678WW	C	10	800	3000	graphite black	154	110	780	1/6	A++→A

Material: Alu+PC | **Chip:** Epistar 2835 SMD | 45PCS 2835 SMD, 10W, 800lm

~230V | 50/60 Hz | SMD 2835 | 30000h | >20000 | IP 54 | Ra>80 | Hg | RoHS COMPLIANT | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



GRF302 LED
96LEDW302

GRF302 LED
96LEDP30278

LED NEUTRAL WHITE 4000K **IP54**

GRF302 LED

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96LEDW302	C	10	800	4000	graphite black	82	284	126	1/12	A++→A
96LEDP30278	C	10	800	4000	graphite black	82	284	780	1/6	A++→A

Material: Alu+PC | **Chip:** Epistar 2835 SMD | 45PCS 2835 SMD, 10W, 800lm

~230V | 50/60 Hz | SMD 2835 | 30000h | >20000 | IP 54 | Ra>80 | RoHS COMPLIANT | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GRF506 LED
96LEDW506

GRF506 LED
96LEDP50678

LED NEUTRAL WHITE 4000K **IP54**

GRF506 LED

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96LEDW506	C	10	800	4000	graphite black	157	92	83	1/16	A++→A
96LEDP50678	C	10	800	4000	graphite black	157	92	787	1/6	A++→A

Material: Alu+PC | **Chip:** Epistar 2835 SMD | 45PCS 2835 SMD, 10W, 800lm

~230V | 50/60 Hz | SMD 2835 | 30000h | >20000 | IP 54 | Ra>80 | Hg | RoHS COMPLIANT | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GRF307 LED

96LEDW307/BL

LED NEUTRAL WHITE 4000K **IP54**

GRF307 LED

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96LEDW307/BL	C	6	600	4000	165	700	1/6	A++→A

Material: UV resistant PP + PC | **Input voltage:** 220-240VAC | **LED Chip:** 2835 SMD | **Mounting:** Surface

~230V | 50/60 Hz | SMD 2835 | RoHS COMPLIANT | 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LUCIA
95LUCIA/BL

GABRI
96GABRI/BL

BEPPE 50W
96BEPPE40/BL

IP66 **IP65** **Resin**

GABRI / LUCIA / BEPPE 50W

Catalogue number	Product category	Model	Lamp included	Colour body	Body material	IP Rating	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96GABRI/BL	C	Bollard	no	black	Resin	IP 66	750		750	1/24	A++→C
95LUCIA/BL	C	Bulkhead	no	black	Resin	IP 66	300	175	255	1/16	A++→C
96BEPPE40/BL	C	Post	yes	black	Resin	IP 65	3065		3065	1/1	A+ A++→A

96GABRI/BL: UV resistant | Lamp not included

96BEPPE40/BL: UV resistant | Lamp included 50 W / 5000 lm / 4000K

Recommended bulbs for **96GABRI/BL** and **95LUCIA/BL**:

99LED588 LED PEAR A60 12W 4000K | **99LED587** LED PEAR A60 12W 2700K | **99LED821** LED PEAR A60 12W 6400K

~230V | 50/60 Hz | E27 | 1,5mm² | RoHS COMPLIANT | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

ST53B
99DS204

ST92
99DS206

ST53M
99DS205

LED NEUTRAL WHITE 4000K **SENSOR** **IP54** **IP65**

ST53B LED / ST53M LED / ST92 LED WITH SENSORS

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	IP rate	Colour body	Length (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99DS204	C	ST53B	15	1200	4000	IP54	white	66	250	1/20	A++→A
99DS205	C	ST53M	20	2300	4000	IP65	white	66	250	1/20	A++→A
99DS206	C	ST92	20	1800	4000	IP65	white	195.5	82	1/10	A++→A

Body material: PC + Aluminium | **Detection distance:** max. 9m | **Detection range:** 140° | **Ambient light:** <3-2000LUX | **Time delay ST53B & ST92:** 10sec±3sec to 5min±1min(adjustable) | **Time delay ST53M:** 10sec±3sec to 15min±2min

~230V | 50/60 Hz | SMD 2835 | RoHS | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

BELT LIGHT

961527

IP44

BELT LIGHT

Catalogue number	Product category	Cable length (m)	Cable specification	Lamp holder	QTY of lamp holder	IP	Packing/Box (pcs)	Energy class
961527	C	5	H05RN-F 2x1.0mm²	E27	15	44	1/5	A++→E

Length 5m / 15 lamps holders

Voltage: 220-240V AC | **Conectors type:** 3 pcs male/female | **Lamps not included**

IP 44 RoHS CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MIRELLA
955MIRELLAWL/GR

SAURO
95SAURO500L/GR

SAURO
95SAURO800L/BL

SAURO
95SAURO1100L/BL

IP55 **Resin**

SAURO/MIRELLA

Catalogue number	Product category	Model	Colour body	Length/ Diameter (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
95SAURO500L/BL	C	SAURO 500	Black	150	500	1xE27	1	A++→C
95SAURO500L/GR	C	SAURO 500	Grey	150	500	1xE27	1	A++→C
95SAURO800L/BL	C	SAURO 800	Black	150	800	1xE27	1	A++→C
95SAURO800L/GR	C	SAURO 800	Grey	150	800	1xE27	1	A++→C
95SAURO1100L/BL	C	SAURO 1100	Black	150	1100	1xE27	1	A++→C
95SAURO1100L/GR	C	SAURO 1100	Grey	150	1100	1xE27	1	A++→C
955MIRELLAWL/BL	C	MIRELLA	Black	240	520	1xE27	1	A++→C
955MIRELLAWL/GR	C	MIRELLA	Grey	240	520	1xE27	1	A++→C

Body: Resin with white resin louvre | UV resistant | Lamp not included

Recommended bulbs:
99LED588 LED PEAR A60 12W 4000K | 99LED587 LED PEAR A60 12W 2700K | 99LED821 LED PEAR A60 12W 6400K

~230V | 50/60 Hz | 1,5mm² | RoHS | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

CARLO DECO
95CARLOWLDFS/BL

CARLO DECO
95CARLOWLD/BL

CARLO DECO
95CARLO800D/BL

CARLO DECO
95CARLO400D/BL

LED 3000 K 4000 K **IP55** **Resin**

CARLO DECO

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Width / Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95CARLO800D/BL	C	6	600	2700/4000 settable	Black	100	800	1/6	A+ A++→A
95CARLO400D/BL	C	6	600	2700/4000 settable	Black	100	400	1/12	A+ A++→A
95CARLOWLD/BL	C	6	600	2700/4000 settable	Black	110	260	1/20	A+ A++→A
95CARLOWLDFS/BL	C	6	600	2700/4000 settable	Black	170	340	1/20	A+ A++→A

Body: Resin with clear glass | UV resistant | **Lamp holder:** G10 | **Lamp included**

The product CARLO is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED729 GU10 LED SMD 7W 4000K | **99XLED730** GU10 LED SMD 7W 2700K | **99XLED796** GU10 LED SMD 7W 6400K

~230V 50/60 Hz 1,5mm² RoHS 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

CARLO DECO
95CARLOWLFS/BL

CARLO
95CARLOWL/BL

CARLO
95CARLO800/BL

CARLO
95CARLO400/BL

LED | 3000 K | 4000 K | IP55 | Resin

CARLO

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Width / Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95CARLO800/BL	C	6	600	2700/4000 settable	Black	100	800	1/6	A+ A++→A
95CARLO400/BL	C	6	600	2700/4000 settable	Black	100	400	1/12	A+ A++→A
95CARLOWL/BL	C	6	600	2700/4000 settable	Black	110	260	1/20	A+ A++→A
95CARLOWLFS/BL	C	6	600	2700/4000 settable	Black	170	340	1/20	A+ A++→A

Body: Resin with clear glass | UV resistant | **Lamp holder:** G10 | **Lamp included**

The product CARLO is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED729 GU10 LED SMD 7W 4000K | **99XLED730** GU10 LED SMD 7W 2700K | **99XLED796** GU10 LED SMD 7W 6400K

~230V | 50/60 Hz | 1,5mm² | RoHS COMPLIANT | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

CARLO
95CARLOWLFS/GR

CARLO
95CARLOWL/GR

CARLO
95CARLO800/GR

CARLO
95CARLO400/GR

LED 3000 K 4000 K **IP55** **Resin**

CARLO

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Width / Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95CARLO800/GR	C	6	600	2700/4000 settable	Grey	100	800	1/6	A+ A++→A
95CARLO400/GR	C	6	600	2700/4000 settable	Grey	100	400	1/12	A+ A++→A
95CARLOWL/GR	C	6	600	2700/4000 settable	Grey	110	260	1/20	A+ A++→A
95CARLOWLFS/GR	C	6	600	2700/4000 settable	Black	170	340	1/20	A+ A++→A

Body: Resin with clear glass | UV resistant | **Lamp holder:** G10 | **Lamp included**

The product CARLO is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED729 GU10 LED SMD 7W 4000K | **99XLED730** GU10 LED SMD 7W 2700K | **99XLED796** GU10 LED SMD 7W 6400K

~230V | 50/60 Hz | 1,5mm² | RoHS COMPLIANT | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

ESTER
95ESTER800/BL

ESTER
95ESTER500/BL

ESTER
95ESTERWL/BL

SAURO
95SAURO800/BL

LED | 3000 K | 4000 K | 6000 K | IP55 | Resin

ESTER/ SAURO

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length/ Diameter (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95ESTER800/BL	C	10	1200	3000/4000/6500- settable	Black	126	126	800	1/6	A+ A++→A
95ESTER500/BL	C	10	1200	3000/4000/6500- settable	Black	126	126	480	1/12	A+ A++→A
95ESTERWL/BL	C	10	1200	3000/4000/6500- settable	Black	126	165	126	1/18	A+ A++→A
95SAURO800/BL	C	10	1200	3000/4000/6500- settable	Black	150		800	1/6	A+ A++→A

Body: Resin with clear glass | UV resistant | **Lamp holder:** GX53 | **Lamp included**

~230V | 50/60 Hz | 1,5mm² | RoHS | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

ESTER
95ESTER800/GR

ESTER
95ESTER500/GR

ESTER
95ESTERWL/GR

LED | 3000 K | 4000 K | 6000 K | IP55 | Resin

ESTER

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length/ Diameter (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95ESTER800/GR	C	10	1200	3000/4000/6500- settable	Grey	126	126	800	1/6	A+ A++→A
95ESTER500/GR	C	10	1200	3000/4000/6500- settable	Grey	126	126	480	1/12	A+ A++→A
95ESTERWL/GR	C	10	1200	3000/4000/6500- settable	Grey	126	165	126	1/18	A+ A++→A

Body: Resin with clear glass | UV resistant | **Lamp holder:** GX53 | **Lamp included**

~230V | 50/60 Hz | 1,5mm² | RoHS COMPLIANT | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

GRF966
966W250

GRF966
966P500

GRF966
966P300

GRF966
966P800

IP65

GRF966

Catalogue number	Product category	Model	Watt (W)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
966W250	C	GRF966-W	MAX 18W	dark grey	250	72	107	1/16	A++→C
966P300	C	GRF966-30	MAX 18W	dark grey	300	72	72	1/9	A++→C
966P500	C	GRF966-50	MAX 18W	dark grey	500	72	72	1/9	A++→C
966P800	C	GRF966-80	MAX 18W	dark grey	800	72	72	1/9	A++→C

Body: aluminium | **Diffuser:** polycarbonate (PC) | **Operating temperature:** -20°C÷+65°C

~230V | 50/60 Hz | CFL | E27 | 1,5mm² | IP 65 | RoHS COMPLIANT | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GRF965
965W200

GRF965
965P500

GRF965
965P300

GRF965
965P800

IP65

GRF965

Catalogue number	Product category	Model	Watt (W)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
965W200	C	GRF965	MAX 23W	dark grey	200	175	190	1/8	A++→C
965P300	C	GRF965-30	MAX 23W	dark grey	300	175	-	1/8	A++→C
965P500	C	GRF965-50	MAX 23W	dark grey	500	175	-	1/4	A++→C
965P800	C	GRF965-80	MAX 23W	dark grey	800	175	-	1/4	A++→C

Body: aluminium | Diffuser: polycarbonate (PC) | Operating temperature: -20°C÷+65°C

~230V | 50/60 Hz | CFL | E27 | 1,5mm² | IP 65 | RoHS | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

PMMA CLEAR
96400023A60LED

PMMA CLEAR
96400024G95LED
96400025G95LED

PMMA CLEAR
9640002730LED
9640002740LED

LED NEUTRAL WHITE 4000K **IP65**

PMMA CLEAR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour aluminium ring	Diameter (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96400023A60LED	C	18	1700	4000	clear	200	100	210	1/16	A+ A++→A
96400024G95LED	C	20	1800	4000	clear	250	125	260	1/12	A+ A++→A
96400025G95LED	C	20	1800	4000	clear	300	145	310	1/6	A+ A++→A
9640002730LED	C	30	2700	4000	clear	400	220	410	1/2	A+ A++→A
9640002740LED	C	40	3600	4000	clear	400	220	410	1/2	A+ A++→A

Diffuser: PMMA (polymethil methacrilate) | **Lamp holder:** E27 | **Mounting:** Metal pole ϕ60

SP60 METAL POLE
Colour: black
Size (mm):
Diameter 60 x Base Ø 145
Product category: G
Height: 600 - **93SP60BL**
Height: 800 - **93SP80BL**
Height: 1000 - **93SP100BL**
Height: 1200 - **93SP120BL**

~230V | E27 | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | F | CE | 2+1 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

PMMA OPAL
96300016
96300017
96300018
96300019

PMMA CLEAR
96400023
96400024
96400025
96400027

IP65

PMMA OPAL / CLEAR

Catalogue number	Product category	Watt (W)	Colour	Diameter (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96300016	C	max 11W	opal	200	100	210	1/16	A++→B
96300017	C	max 15W	opal	250	125	260	1/12	A++→B
96300018	C	max 20W	opal	300	145	310	1/6	A++→B
96300019	C	max 40W	opal	400	220	410	1/2	A++→B
96400023	C	max 11W	clear	200	100	210	1/16	A++→B
96400024	C	max 15W	clear	250	125	260	1/12	A++→B
96400025	C	max 20W	clear	300	145	310	1/6	A++→B
96400027	C	max 40W	clear	400	220	410	1/2	A++→B

Diffuser: PMMA (polymethil methacrilate) | **Lamp holder:** E27 | **Mounting:** Metal pole ϕ60 | Lamps not included

SP60 METAL POLE
Colour: black
Size (mm):
Diameter 60 x Base Ø 145
Product category: G
Height: 600 - **93SP60BL**
Height: 800 - **93SP80BL**
Height: 1000 - **93SP100BL**
Height: 1200 - **93SP120BL**

~230V | E27 | IP 65 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GRF
96GRFLED0091

GRF
96GRFLED0041
96GRFLED0031

LED COOL WHITE 6400K **IP65**

GRF LED RECESSED FIXTURES

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Light angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96GRFLED0031	C	1,5	55/32	6000-6500	30°	120	53	61	1/50	A++→A
96GRFLED0091	C	1,5	75/42	6000-6500	30°	80	80	61	1/50	A++→A
96GRFLED0041	C	3,5	187/165	6000-6500	30°	205	95	65	1/27	A++→A

Body: Stainless steel +Aluminium | **Cable:** 3G0.75mm2-10cm | **Light source:** SMD2835 | **LED driver:** mounted in the body
Operating temperature: -20°C÷+65°C

*Until Supply Last

Each of the models comes with additional decorative grid, shown in the picture.

~230V 50/60 Hz Ra>80 >15000 INSTANT 100% 30000h Hg IP 65 RoHS COMPLIANT EMC 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

NINA 150
96NINA150/BL

NINA 150
96NINA150/GR

NINA 190
96NINA190/BL



NINA 190
96NINA190/GR

LED | 3000 K | 4000 K | 6000 K | IP55 | Resin

NINA 150 / NINA 190

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96NINA150/BL	C	3,2	400	3000/4000/6500- SETTABLE	black	145	50	50	1	A+ A+→A
96NINA150/GR	C	3,2	400	3000/4000/6500- SETTABLE	grey	145	50	50	1	A+ A+→A
96NINA190/BL	C	7,5	850	3000/4000/6500- SETTABLE	black	185	50	50	1/50	A+ A+→A
96NINA190/GR	C	7,5	850	3000/4000/6500- SETTABLE	grey	185	50	50	1/50	A+ A+→A

Body: Resin | **Lamp holder:** R7s | Lamp included

~230V | 50/60 Hz | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days. .

LED WALL FIXTURE 1.5W
96GRFLED52/DGR

LED WALL FIXTURES 1.8W
96GRFLED02/WH

LED NEUTRAL WHITE 4000K **IP65**

GRF LED WALL FIXTURES

Catalogue number WHITE	Catalogue number GREY	Catalogue number DARK GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
96GRFLED52/WH	**96GRFLED52/GR**	**96GRFLED52/DGR**	C	1.5	60	4000	125	125	20.5	1/40	A++→A
96GRFLED02/WH	**96GRFLED02/GR**	**96GRFLED02/DGR**	C	1.8	90	4000	230	80	16.5	1/24	A++→A

Body material: ABS | **Diffuser:** PVC | **Light source:** 2835 SMD
Light source: LED type Φ5mm recessed fixture | **Operating temperature:** -20°C÷+65°C

~230V | 50/60 Hz | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | CE | 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

WALL LAMP GRF LED
96GRFLED01/1GR

WALL LAMP GRF LED
96GRFLED309/4BL



WALL LAMP GRF LED
96GRFLED308/4GR

LED NEUTRAL WHITE 4000K **IP65**

WALL LAMP GRF LED

Catalogue number BLACK	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
96GRFLED308/4BL	**96GRFLED308/4GR**	C	4	300	4000	230	80	27	1/24	A++→A
96GRFLED01/1BL	**96GRFLED01/1GR**	C	1	30	4000	80	200	27	1/24	A++→A
96GRFLED309/4BL	**96GRFLED309/4GR**	C	4	280	4000	125	125	27	1/40	A++→A

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **LED Chip:** 2835 SMD | **Mounting:** Surface

~230V 50/60 Hz Ra>80 RoHS EMC CE 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LETI 100
96LETI100/BL
96LETI100/GR

LETI 100GR
96LETI100GR/BL
96LETI100GR/GR

LETI 100EL
96LETI100EL/BL
96LETI100EL/GR

LED | 3000 K | 4000 K | 6000 K | IP66 | Resin

LETI 100

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Diameter 1 (mm)	Width (mm)	Packing/Box (pcs)	Energy class
96LETI100/BL	C	LETI 100	3	350	3000/4000/6500- settable	Black	134	96	80	1/48	A+ A++→A
96LETI100/GR	C	LETI 100	3	350	3000/4000/6500- settable	Grey	134	96	80	1/48	A+ A++→A
96LETI100GR/BL	C	LETI 100GR	3	350	3000/4000/6500- settable	Black	134	96	80	1/48	A+ A++→A
96LETI100GR/GR	C	LETI 100GR	3	350	3000/4000/6500- settable	Grey	134	96	80	1/48	A+ A++→A
96LETI100EL/BL	C	LETI 100EL	3	350	3000/4000/6500- settable	Black	134	96	80	1/48	A+ A++→A
96LETI100EL/GR	C	LETI 100EL	3	350	3000/4000/6500- settable	Grey	134	96	80	1/48	A+ A++→A

Body: Resin with opal glass | **UV resistant** | **Lamp holder:** GX53 | Lamp included

~230V | 50/60 Hz | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days. .

EXTRALETI 100EL
96LETI100REL/BL
96LETI100REL/GR

EXTRALETI 100GR
96ELETI100RGR/BL
96ELETI100RGR/GR

LED 3000 K 4000 K 6000 K **IP66** **Resin**

EXTRALETI 100

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96ELETI100RGR/BL	C	EXTRALETI 100GR	3	350	2700/4000/6500 SETTABLE	Black	140	67	1/48	A+ A++→A
96ELETI100RGR/GR	C	EXTRALETI 100GR	3	350	2700/4000/6500 SETTABLE	Grey	140	67	1/48	A+ A++→A
96LETI100REL/BL	C	EXTRALETI 100EL	3	350	2700/4000/6500 SETTABLE	Black	140	67	1/48	A+ A++→A
96LETI100REL/GR	C	EXTRALETI 100EL	3	350	2700/4000/6500 SETTABLE	Grey	140	67	1/48	A+ A++→A

Body: Resin with opal glass | **UV resistant** | **Lamp holder:** GX53 | Lamp included

~230V 50/60 Hz Ra>80 >15000 INSTANT 100% 30000h Hg RoHS COMPLIANT F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days. .

LETI 300HVP
96LETI300HVP/BL



LETI 300GL
96LETI300GL/BL

LETI 300HS
96LETI300VP/BL
96LETI300VP/GR

LETI 300
96LETI300/BL
96LETI300/GR

IP66 **Resin**

LETI 300

Catalogue number	Product category	Model	Colour body	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96LETI300/BL	C	LETI 300	Black	293	113	98	1xE27	1/24	A++→C
96LETI300/GR	C	LETI 300	Grey	293	113	98	1xE27	1/24	A++→C
96LETI300GL/BL	C	LETI 300GL	Black	293	113	98	1xE27	1/24	A++→C
96LETI300VP/BL	C	LETI 300HS	Black	293	113	98	1xE27	1/24	A++→C
96LETI300VP/GR	C	LETI 300HS	Grey	293	113	98	1xE27	1/24	A++→C
96LETI300HVP/BL	C	LETI 300HVP	Black	113	293	98	1xE27	1/24	A++→C
96LETI300HVP/GR	C	LETI 300HVP	Grey	113	293	98	1xE27	1/24	A++→C

Body: Resin with opal glass | **UV resistant** | Lamp not included

RoHS COMPLIANT CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days. .

WALL LAMP GRF LED
96GRFLED302/6BL

WALL LAMP GRF LED
96GRFLED301/6BL

WALL LAMP GRF LED
96GRFLED300/6BL

LED NEUTRAL WHITE 4000K **IP65**

WALL LAMP GRF LED

Catalogue number BLACK	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
96GRFLED300/6BL	**96GRFLED300/6GR**	C	6	330	4000	255	90	42	1/20	A++↦A
96GRFLED301/6BL	**96GRFLED301/6GR**	C	6	120	4000	255	90	42	1/20	A++↦A
96GRFLED302/6BL	**96GRFLED302/6GR**	C	6	110	4000	255	90	42	1/20	A++↦A

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | High voltage PCB | **LED Chip:** 2835 SMD | **Mounting:** Surface

~230V 50/60 Hz Ra>80 Hg RoHS EMC F CE 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

WALL LAMP GRF LED
96GRFLED310/8GR

WALL LAMP GRF LED
96GRFLED311/8BL

LED NEUTRAL WHITE 4000K **IP65**

WALL LAMP GRF LED

Catalogue number BLACK	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
96GRFLED310/8BL	**96GRFLED310/8GR**	C	8	260	4000	200	200	55	1/20	A++→A
96GRFLED311/8BL	**96GRFLED311/8GR**	C	8	250	4000	230		55	1/20	A++→A

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **LED Chip:** 2835 SMD | **Mounting:** Surface

~230V 50/60 Hz Ra>80 RoHS EMC F CE 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

WALL LAMP GRF LED
96GRFLED303/6BL

WALL LAMP GRF LED
96GRFLED304/6BL

LED NEUTRAL WHITE 4000K **IP65**

WALL LAMP GRF LED

Catalogue number BLACK	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
96GRFLED303/6BL	**96GRFLED303/6GR**	C	6	200	4000	135	135	42	1/20	A++→A
96GRFLED304/6BL	**96GRFLED304/6GR**	C	6	100	4000	135	135	42	1/20	A++→A

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **LED Chip:** 2835 SMD | **Mounting:** Surface

~230V 50/60 Hz Ra>80 Hg RoHS EMC F CE 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LORENZA 150
95LORENZA150/BL

LORENZA 150
95LORENZA150/GR

LORENZA 190
95LORENZA190/BL

LORENZA 190
95LORENZA190/GR

LED | 3000 K | 4000 K | 6000 K | IP55 | Resin

LORENZA

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
95LORENZA150/BL	C	LORENZA 150	3.2	400	3000/4000/6500 - settable	Black	150	150	45	1/24	A+ A++→A
95LORENZA150/GR	C	LORENZA 150	3.2	400	3000/4000/6500 - settable	Grey	150	150	45	1/24	A+ A++→A
95LORENZA190/BL	C	LORENZA 190	7.5	850	3000/4000/6500 - settable	Black	190	150	45	1/24	A+ A++→A
95LORENZA190/GR	C	LORENZA 190	7.5	850	3000/4000/6500 - settable	Grey	190	150	45	1/24	A+ A++→A

Body material: Resin with clear glass | **UV resistant** | **Lamp holder:** R7s | **Lamp included**

~230V | 50/60 Hz | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LORENZA 270
95LORENZA270/BL

LORENZA 270
95LORENZA270/GR

LED 3000 K 4000 K 6000 K **IP55** **Resin**

LORENZA 270

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
95LORENZA270/BL	C	LORENZA 270	10,5	1100	3000/4000/6500 - settable	Black	260	150	45	1/14	A+ A++→A
95LORENZA270/GR	C	LORENZA 270	10,5	1100	3000/4000/6500 - settable	Grey	260	150	45	1/14	A+ A++→A

Body material: Resin with clear glass | **UV resistant** | **Lamp holder:** R7s | **Lamp included**

~230V | 50/60 Hz | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ABRAM 150
95ABRAM150/BL

ABRAM 150
95ABRAM150/GR

ABRAM 190
95ABRAM190/BL

ABRAM 190
95ABRAM190/GR

LED | 3000 K | 4000 K | 6000 K | IP55 | Resin

ABRAM

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
95ABRAM150/BL	C	ABRAM 150	3.2	400	3000/4000/6500 - settable	Black	155	60	120	1/30	A+ A++→A
95ABRAM150/GR	C	ABRAM 150	3.2	400	3000/4000/6500 - settable	Grey	155	60	120	1/30	A+ A++→A
95ABRAM190/BL	C	ABRAM 190	7.5	850	3000/4000/6500 - settable	Black	195	60	120	1/30	A+ A++→A
95ABRAM190/GR	C	ABRAM 190	7.5	850	3000/4000/6500 - settable	Grey	195	60	120	1/30	A+ A++→A

Body material: Resin with clear glass | **UV resistant** | **Lamp holder:** R7s | **Lamp included**

~230V | 50/60 Hz | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED WALL LIGHT
ROUND IP54
White / Black / Grey

LED WALL LIGHT
SQUARE IP54
White / Black / Grey

LED WALL LIGHT
ROUNDED IP65
White / Black / Grey

LED NEUTRAL WHITE 4000K **IP54** **IP65**

LED WALL LIGHT

Catalogue number	Product category	Watt (W)	Type	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
969LED100R/WH	C	2X5W	Round	900	4000	white	130	110	100	1/12	A++→A
969LED100R/BL	C	2X5W	Round	900	4000	black	130	110	100	1/12	A++→A
969LED100R/GR	C	2X5W	Round	900	4000	grey	130	110	100	1/12	A++→A
969LED100S/WH	C	2X5W	Square	900	4000	white	100	100	100	1/10	A++→A
969LED100S/BL	C	2X5W	Square	900	4000	black	100	100	100	1/10	A++→A
969LED100S/GR	C	2X5W	Square	900	4000	grey	100	100	100	1/10	A++→A
969LEDW12/WH	C	**2X6W**	Rounded	1080	4000	white	175	28	90	1/40	A++→A
969LEDW12/BL	C	**2X6W**	Rounded	1080	4000	black	175	28	90	1/40	A++→A
969LEDW12/GR	C	**2X6W**	Rounded	1080	4000	grey	175	28	90	1/40	A++→A

Body material: Aluminium | **Diffuser:** Glass | **Light source 969led100:** Epistar LED COB **Light source 969LEDW12:** Epistar SMD2835

~230V 50/60 Hz Ra>80 30000h RoHS EMC 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

WALL LAMP
95WL001/BL

WALL LAMP
95WL001/WH

IP44

GARDEN WALL LAMP E27

Catalogue number	Product category	Description	Colour	Widthr (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
95WL001/BL	C	Wall lamp	Black	245	180	100	1 x E27	1/10	A++→E
95WL001/WH	C	Wall lamp	White	245	180	100	1 x E27	1/10	A++→E

Voltage: 220-240V AC | Lamps not included

IP 44 RoHS COMPLIANT CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GARDEN WALL LAMP
95WL315/BL

IP65

GARDEN WALL LAMP E27

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Widthr (mm)	Lampholder	Packing/Box (pcs)	Energy class
95WL315/BL	C	Wall lamp	Black	170	170	140	1XE27	1/12	A++→E
95WL315/WH	C	Wall lamp	White	170	170	140	1XE27	1/12	A++→E

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TINA IP65
95TINA12/BL

LED WALL FIXTURE 6W IP65
96GRFLED05/GR

FRANCY IP66
95FRANCY/BL

LED | NEUTRAL WHITE 4000K | **IP65** | **IP66** | **Resin**

FRANCY / GRF LED / TINA

Catalogue number BLACK body	Catalogue number WHITE body	Catalogue number GREY body	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length / diameter (mm)	Width (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
95FRANCY/BL	**95FRANCY/WH**		C	6	800	4000	300	85	130	1xE27	1/24	A+ A++→A
96GRFLED05/DGR	**96GRFLED05/WH**	**96GRFLED05/GR**	C	6	480	4000	220	28	113		1/20	A++→A
95TINA12/BL			C	12	1080	4000	230	72	105		1	A+ A++→A

FANCY, TINA: Body material: Resin | UV resistant
GRF LED: Body material: ABS | **Diffuser:** PVC | **Light source:** 2835 SMD

The product is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99LED583 LED PEAR A60 8W 2700K | **99LED584** LED PEAR A60 8W 6400K | **99LED794** LED PEAR A60 8W 6400K

99LED588 LED PEAR A60 12W 4000K | **99LED587** LED PEAR A60 12W 2700K | **99LED821** LED PEAR A60 12W 6400K

~230V | 50/60 Hz | 1,5mm² | RoHS COMPLIANT | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of FRANCY IP66 the delivery time after order confirmation will be 45 days, and for others products 90 days.

STUCCHI
95STUCCHI/BL

BERTA
95BERTA/BL

IP66 **Resin**

BERTA / STUCCHI

Catalogue number BLACK body	Catalogue number WHITE body	Product category	Description	Length / diameter (mm)	Width (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
95BERTA/BL	**95BERTA/WH**	C	BULKHEAD	275	80	275	1xE27	1/16	A++→C
95STUCCHI/BL	**95STUCCHI/WH**	C	BULKHEAD WITH BACKLIGHT	310	90	338	1xE27+ backlights	1/16	A++→C

Body material: Resin| UV resistant | Lamp not included

Recommended bulbs:

99LED588 LED PEAR A60 12W 4000K | **99LED587** LED PEAR A60 12W 2700K | **99LED821** LED PEAR A60 12W 6400K

~230V | 50/60 Hz | E27 | Ra>80 | 30000h | Hg | RoHS | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

UMBERTA
95UMBERTA/BL
95UMBERTAS/BL

UMBERTA
95UMBERTA/WH
95UMBERTAS/WH

IP66 **Resin**

UMBERTA

Catalogue number	Product category	Model	Colour body	Lampholder	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95UMBERTA/BL	C	BULKHEAD	Black	2xE27	350	94	1/12	A++→C
95UMBERTA/WH	C	BULKHEAD	White	2xE27	350	94	1/12	A++→C
95UMBERTAS/BL	C	BULKHEAD WITH SENSOR	Black	2xE27	350	94	1/12	A++→C
95UMBERTAS/WH	C	BULKHEAD WITH SENSOR	White	2xE27	350	94	1/12	A++→C

Body: Resin with opal diffuser | **UV resistant** | Sensor: Motion & daylight | **Detection angle:** 30° - 150° | **Fields of detection:** from 1 up to 5 mt (adjustable) | **Lamp holder:** E27 | Lamp not included

Recommended bulbs:

99LED588 LED PEAR A60 12W 4000K | **99LED587** LED PEAR A60 12W 2700K | **99LED821** LED PEAR A60 12W 6400K

~230V | 50/60 Hz | E27 | RoHS | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

LUCIA
95LUCIA/BL

LUCIA EL
95LUCIAEL/BL

IP66 **Resin**

LUCIA / LUCIA EL

Catalogue number	Product category	Colour	Diameter (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
95LUCIA/BL	C	Black	300	175	1xE27	1/16	A++→C
95LUCIAEL/BL	C	Black	300	90	1xE27	1/16	A++→C
95LUCIAEL/GR	C	Grey	300	90	1xE27	1/16	A++→C

Body: Resin with opal glass | **UV resistant** | **Lamp not included**



Recommended bulbs:
99LED588 LED PEAR A60 12W 4000K
99LED587 LED PEAR A60 12W 2700K
99LED821 LED PEAR A60 12W 6400K

~230V | 50/60 Hz | E27 | Ra>80 | 30000h | Hg | RoHS | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FRANCY OP IP66
95FRANCYOP/WH

BRLED ROUND
95BRLED6BL
95BRLED12WH
95BRLED12BL

BRLED OVAL
95BELED6WH
95BELED6BL
95BELED12WH
95BELED12BL

LED NEUTRAL WHITE 4000K **IP54** **IP66**

BRLED / FRANCY OP

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	IP code	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95BRLED6BL	F	6*	540	4000	black	54	170	170	100	1/24	A++→A
95BRLED12BL	F	12*	1080	4000	black	54	220	220	100	1/24	A++→A
95BELED6WH	F	6*	540	4000	white	54	187	127	100	1/24	A++→A
95BELED6BL	F	6*	540	4000	black	54	187	127	100	1/24	A++→A
95BELED12WH	F	12*	1080	4000	white	54	239	162	100	1/24	A++→A
95BELED12BL	F	12*	1080	4000	black	54	239	162	100	1/24	A++→A
95FRANCYOP/BL	C	empty			black	66	300	85	130	1/24	A++→C
95FRANCYOP/WH	C	empty			white	66	300	85	130	1/24	A++→C

BRLED: Body: polycarbonate | **LED driver:** mounted in the body | **Light source:** EPISTAR | *Until supply last
FRANCY OP: Body material: Resin | UV resistant | Lamp not included

Recommended bulbs:
99LED588 LED PEAR A60 12W 4000K
99LED587 LED PEAR A60 12W 2700K
99LED821 LED PEAR A60 12W 6400K

~230V | 50/60 Hz | E27 | Ra>80 | 30000h | Hg | RoHS | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

BRICE
95BRICE12LED

BRICE
95BRICE24LED

LED NEUTRAL WHITE 4000K **IP44**

BRICE

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	IP code	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95BRICE12LED	C	12	1080	4000	white	44	260	260	90	1/16	A++→A
95BRICE24LED	C	24	2160	4000	white	44	380	380	110	1/10	A++→A

Body: polycarbonate | **LED driver:** mounted in the body | **Light source:** EPISTAR

~230V 50/60 Hz SMD Ra>80 30000h Hg RoHS COMPLIANT EMC CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED BULKHEAD LAMP
BLACK / WHITE
95BLN1540/WH
95BLN1540/BK
95BLN2040/WH
95BLN2040/BK

LED BULKHEAD LAMP
95BSLED12WH

LED BULKHEAD LAMP
BLACK / WHITE
95BLN1540S/WH
95BLN1540S/BK

NEUTRAL WHITE 4000K | IP54

LED BULKHEAD LAMP

Catalogue number	Product category	Watt (W)	Whole fixtures lumens (lm)	Colour temp. (K)	Colour of body	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
95BSLED12WH	F*	12	1080	4500	white	220	78	143	143	A++→A
95BLN1540/WH	C	15	1350	4000	white	175	52	175	1/40	A++→A
95BLN1540/BK	C	15	1350	4000	black	175	52	175	1/40	A++→A
95BLN2040/WH	C	20	1800	4000	white	210	52	210	1/20	A++→A
95BLN2040/BK	C	20	1800	4000	black	210	52	210	1/20	A++→A
95BLN1540S/WH	C	15	1350	4000	white	200	46	98	1/40	A++→A
95BLN1540S/BK	C	15	1350	4000	black	200	46	98	1/40	A++→A

Body: polycarbonate | **LED driver:** linear I C driver | **Light source:** 2835SMD | * Until Supply Last



ULTRA THIN

EASY INSTALLATION

BACK HIDDEN CABLE

~230V | 50/60 Hz | SMD | Ra>80 | 30000h | IP 54 | RoHS | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

WALL LAMPS ST73
99DS203

WALL LAMPS ST72
99DS202

LED NEUTRAL WHITE 4000K **SENSOR** **IP54**

WALL LAMPS ST73 AND ST72 WITH SENSORS

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Width (mm)	Height (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99DS202	C	ST72	15	1100	4000	white	119.2	44.5	212.2	1/20	A++→A
99DS203	C	ST73	15	1100	4000	white	210	210	49	1/20	A++→A

Body material: PC | **Detection distance:** max. 9m | **Detection range:** 140° | **Ambient light:** <3-2000LUX | **Time delay:** 10sec±3sec to 5min±1min(adjustable)

~230V | 50/60 Hz | SMD 2835 | RoHS COMPLIANT | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GRF9617 LED
9617LEDW

GRF9617 LED
9619LEDW

GRF9617 LED
9618LEDW

LED NEUTRAL WHITE 4000K **IP54**

UNTIL SUPPLY LAST

GRF9617 LED

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9617LEDW	F	3X3W	480	4000-4300	dark grey	44	138	143	1/24	A++→A
9618LEDW	F	3X3W	480	4000-4300	dark grey	44	138	143	1/24	A++→A
9619LEDW	F	2X3W	380	4000-4300	dark grey	44	138	143	1/24	A++→A



Body: aluminium | **Diffuser:** tempered glass | **LED driver:** mounted in the body | **Light source:** CREE LED
Operating temperature: -20°C÷+65°C

~230V 50/60 Hz Ra>80 >15000 INSTANT 100% 30000h Hg IP 54 RoHS COMPLIANT EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



ARIA
91AT5201

LINIA4
91AT6126

LINIA1
91AT6117

SIRIUS
91AT1210
91AT1209

IP54

SIRIUS / ARIA / LINIA

Catalogue number	Product category	Model	Watt (W)	Colour	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
91AT1210	C	SIRIUS1	MAX 20W	white	230	-	110	1/21	A++→C
91AT1209	C	SIRIUS2	MAX 20W	white	280	-	115	1/14	A++→C
91AT5201	C	ARIA	MAX 23W	white	350	120	80	1/12	A++→C
91AT6117	C	LINIA1	MAX 20W	white	320	137	110	1/26	A++→C
91AT6126	C	LINIA4	MAX 20W	white	320	200	110	1/18	A++→C

Body: polycarbonate (PC) | **Diffuser:** polycarbonate (PC)

*Until Supply Last

~230V | 50/60 Hz | CFL | E27 | IP 54 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.

BULKHEAD LAMP GRF314
96GRF314/BL

IP44

BULKHEAD LAMP GRF314

Catalogue number	Product category	Description	Colour	Length (mm)	Height (mm)	Widthr (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF314/BL	C	Bulkhead lamp	Black	223	128	93	1XE27	1/18	A++→E
96GRF314/WH	C	Bulkhead lamp	White	223	128	93	1XE27	1/18	A++→E

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TERESA
96TERESA/BL

TERESA
96TERESA/GR

TERESA2L
96TERESA2L/BL

TERESA2L
96TERESA2L/GR

LED NEUTRAL WHITE 4000K **IP67** **Resin**

TERESA

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96TERESA/BL	C	1,7	170	4000	Black	50	75	1/75	A+ A++→A
96TERESA/GR	C	1,7	170	4000	Grey	50	75	1/75	A+ A++→A
96TERESA2L/BL	C	1,7	170	4000	Black	50	75	1/75	A+ A++→A
96TERESA2L/GR	C	1,7	170	4000	Grey	50	75	1/75	A+ A++→A

Body: Resin with frosted diffuser | **UV resistant** | **Lamp holder:** G9 | Lamp included

50/60 Hz | IP 67 | RoHS | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of 96GRFLED068 the delivery time after order confirmation will be 90 days, and for others products 45 days.

LIVIA 90
95LIVIA90/BL

LIVIA 90
95LIVIA90/GR

LIVIA 90
95LIVIA90/WH

LED 3000 K 4000 K **IP55** **Resin**

LIVIA 90

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95LIVIA90/BL	C	6	600	2700/4000 settable	Black	96	105	1/75	A+ A++→A
95LIVIA90/GR	C	6	600	2700/4000 settable	Grey	96	105	1/75	A+ A++→A
95LIVIA90/WH	C	6	600	2700/4000 settable	White	96	105	1/75	A+ A++→A

Body: Resin with frosted glass | **UV resistant** | **Lamp holder:** GU10 | Lamp included

~230V 50/60 Hz 1,5mm² RoHS COMPLIANT 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

LIVIA 160
95LIVIA160/BL

LIVIA 160
95LIVIA160/GR

LIVIA 160
95LIVIA160/WH

LED | 3000 K | 4000 K | 6000 K | IP55 | Resin

LIVIA 160

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95LIVIA160/BL	C	10	1200	3000/4000/6500- settable	Black	160	100	1/18	A⁺ A⁺⁺→A
95LIVIA160/GR	C	10	1200	3000/4000/6500- settable	Grey	160	100	1/18	A⁺ A⁺⁺→A
95LIVIA160/WH	C	10	1200	3000/4000/6500- settable	White	160	100	1/18	A⁺ A⁺⁺→A

Body: Resin with frosted glass | **UV resistant** | **Lamp holder:** GX53 | Lamp included

~230V | 50/60 Hz | 1,5mm² | RoHS | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

LIVIA 180
95LIVIA180/BL

LIVIA 180
95LIVIA160/WH

LED NEUTRAL WHITE 4000K **IP43** **Resin**

LIVIA 180

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95LIVIA180/BL	C	15	1800	4000	Black	180	200	1/12	A+ A++→A
95LIVIA180/GR	C	15	1800	4000	Grey	180	200	1/12	A+ A++→A
95LIVIA180/WH	C	15	1800	4000	White	180	200	1/12	A+ A++→A

Body: Resin with frosted glass | **UV resistant** | **Lamp holder:** E27 | Lamp included



~230V 50/60 Hz 1,5mm² RoHS F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

BULKHEAD LIGHTS
96DL305/BL
96DL306/BL

BULKHEAD LIGHTS
96DL305/GR
96DL306/GR

BULKHEAD LIGHTS
96DL305/WH
96DL306/WH

IP54

BULKHEAD LIGHTS

Catalogue number BLACK	Catalogue number GREY	Catalogue number WHITE	Product category	Description	Diameter (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96DL305/BL	**96DL305/GR**	**96DL305/WH**	C	Bulkhead	122	170	1XE27	1/20	A++→A
96DL306/BL	**96DL306/GR**	**96DL306/WH**	C	Bulkhead	72	140	1XGU10	1/20	A++→A

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of FRANCY IP66 the delivery time after order confirmation will be 45 days, and for others products 90 days.

ELMARK

www.elmarkholding.eu

GRF

96GRF1482

IP65

GRF

Catalogue number	Product category	Width (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF1482	C	254	498.5	1482.6	1 x E27	1/2	A++→E

Body: aluminium, antique bronze

220-240V | 50/60 Hz | CFL | E27 | 1,5mm² | IP 65 | RoHS COMPLIANT | F | CE

3+0 standard +extended 3 YEAR TOTAL WARRANTY

98STREAM9
98STREAM9RGB



98STREAM36
98STREAM36RGB

LED **IP65**

STREAM STELLAR

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98STREAM9	C	STREAM9	9	720	5500	grey	300	50	56	1/9	A++→A
98STREAM18	C	STREAM18	18	1440	5500	grey	600	50	56	1/9	A++→A
98STREAM36	C	STREAM36	36	2880	5500	grey	1000	50	56	1/9	A++→A
98STREAM9RGB	C	STREAM9 RGB	9	-	RGB	grey	300	50	56	1/9	A++→A
98STREAM18RGB	C	STREAM18 RGB	18	-	RGB	grey	500	55	60	1/9	A++→A
98STREAM36RGB	C	STREAM36 RGB	36	-	RGB	grey	1000	50	56	1/9	A++→A

Body: aluminium casting | **LED driver:** mounted in the body | **Light source:** Epistar | **Ambient Temperature:** -25°C÷ +55°C

~230V | 50/60 Hz | High power | Ra>70 | 20000h | Hg | IP 65 | RoHS | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FACADE LIGHTING FIXTURES GRF320
96GRF321/BL

FACADE LIGHTING FIXTURES GRF320
96GRF320/BL

FACADE LIGHTING FIXTURES GRF320
96GRF321/GR

FACADE LIGHTING FIXTURES GRF320
96GRF320/GR

IP54

FACADE LIGHTING FIXTURES GRF320 & GRF321

Catalogue number BLACK	Catalogue number GREY	Product category	Description	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF320/BL	**96GRF320/GR**	C	Facade lighting	70	90	92	1xGU10	1/20	A++→E
96GRF321/BL	**96GRF321/GR**	C	Facade lighting	70	160	92	2xGU10	1/20	A++→E

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FACADE LIGHTING
FIXTURES GRF313
96GRF313/BL

FACADE LIGHTING
FIXTURES GRF313
96GRF313/GR

IP65

FACADE LIGHTING FIXTURES GRF313

Catalogue number BLACK	Catalogue number GREY	Product category	Description	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF313/BL	**96GRF313/GR**	C	Facade lighting	230	90	101	1XE27	1/10	A++→E

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FACADE LIGHTING FIXTURES GRF327
96GRF327/BL

FACADE LIGHTING FIXTURES GRF326
96GRF326/BL

FACADE LIGHTING FIXTURES GRF327
96GRF327/GR

FACADE LIGHTING FIXTURES GRF327
96GRF326/GR

IP44

FACADE LIGHTING FIXTURES GRF326 & GRF327

Catalogue number BLACK	Catalogue number GREY	Product category	Description	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF326/BL	**96GRF326/GR**	C	Facade lighting	70	80	95	1xGU10	1/20	A++→E
96GRF327/BL	**96GRF327/GR**	C	Facade lighting	70	150	95	2xGU10	1/20	A++→E

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FACADE LIGHTING FIXTURES GRF322
96GRF322/BL

FACADE LIGHTING FIXTURES GRF323
96GRF323/GR

IP44

FACADE LIGHTING FIXTURES GRF322 & GRF323

Catalogue number BLACK	Catalogue number GREY	Product category	Description	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF322/BL	**96GRF322/GR**	C	Facade lighting	60	100	88	1xGU10	1/16	A++→E
96GRF323/BL	**96GRF323/GR**	C	Facade lighting	60	158	88	2xGU10	1/16	A++→E

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FACADE LIGHTING FIXTURES GRF325
96GRF325/BL

FACADE LIGHTING FIXTURES GRF324
96GRF324/BL

FACADE LIGHTING FIXTURES GRF325
96GRF325/GR

FACADE LIGHTING FIXTURES GRF324
96GRF324/GR

IP54

FACADE LIGHTING FIXTURES GRF324 & GRF325

Catalogue number BLACK	Catalogue number GREY	Product category	Description	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF324/BL	**96GRF324/GR**	C	Facade lighting	90	162	113	1xGU10	1/16	A++→E
96GRF325/BL	**96GRF325/GR**	C	Facade lighting	90	215	113	2xGU10	1/16	A++→E

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MARTA 90-1
96MARTA901L/BL

MARTA 90-2
96MARTA902L/BL

LED | 3000 K 4000 K | IP55 | Resin

UNTIL SUPPLY LAST

MARTA

Catalogue number	Product category	Description	Colour	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Width (mm)	Height (mm)	Lampholder	Packing/ Box (pcs)	Energy class
96MARTA901L/BL	F	Facade lighting	black	1x6	600	2700/4000 settable	92	80	170	1xGU10	1/36	A+ A++→A
96MARTA901L/GR	F	Facade lighting	gray	1x6	600	2700/4000 settable	92	80	170	1xGU10	1/36	A+ A++→A
96MARTA902L/BL	F	Facade lighting	black	2x6	1200	2700/4000 settable	92	80	170	2xGU10	1/36	A+ A++→A
96MARTA902L/GR	F	Facade lighting	gray	2x6	1200	2700/4000 settable	92	80	170	2xGU10	1/36	A+ A++→A

Body material: Resin| UV resistant | **Lamp included** | **Lamp holder:** GU10

The product is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED727 GU10 LED SMD 3.5W 4000K | **99XLED728** GU10 LED SMD 3.5W 2700K | **99XLED731** GU10 LED SMD 3.5W 6400K

99LED729 GU10 LED SMD 6.5W 4000K | **99LED730** GU10 LED SMD 6.5W 2700K | **99LED796** GU10 LED SMD 6.5W 6400K

~230V | 50/60 Hz | 1.5mm² | RoHS COMPLIANT | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

FRANCA 90
96FRANCA90/GR

FRANCA 90-1
96FRANCA901L/BL

FRANCA 90-2
96FRANCA902L/GR

LED | 3000 K 4000 K | IP55 | Resin

UNTIL SUPPLY LAST

FRANCA

Catalogue number	Product category	Description	Colour	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Width (mm)	Height (mm)	Lampholder	Packing/ Box (pcs)	Energy class
96FRANCA90/BL	F	Ceiling fixtures	black	6	600	2700/4000 settable	95		115	1xGU10	1/30	A+ A++→A
96FRANCA90/GR	F	Ceiling fixtures	gray	6	600	2700/4000 settable	95		115	1xGU10	1/30	A+ A++→A
96FRANCA901L/BL	F	Facade lighting	black	6	600	2700/4000 settable	95	110	128	1xGU10	1/30	A+ A++→A
96FRANCA901L/GR	F	Facade lighting	gray	6	600	2700/4000 settable	95	110	128	1xGU10	1/30	A+ A++→A
96FRANCA902L/BL	F	Facade lighting	black	2x6	1200	2700/4000 settable	95	110	240	2xGU10	1/20	A+ A++→A
96FRANCA902L/GR	F	Facade lighting	gray	2x6	1200	2700/4000 settable	95	110	240	2xGU10	1/20	A+ A++→A

Body material: Resin| UV resistant | Lamp included | **Lamp holder:** GU10

The product is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED727 GU10 LED SMD 3.5W 4000K | **99XLED728** GU10 LED SMD 3.5W 2700K | **99XLED731** GU10 LED SMD 3.5W 6400K

99LED729 GU10 LED SMD 6.5W 4000K | **99LED730** GU10 LED SMD 6.5W 2700K | **99LED796** GU10 LED SMD 6.5W 6400K

~230V | 50/60 Hz | 1.5mm² | RoHS COMPLIANT | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

OL9612-W1 LED
9612LEDW1

OL9611-W1 LED
9611LEDW1

OL9612-W2 LED
9612LEDW2

OL9611-W2 LED
9611LEDW2

LED NEUTRAL WHITE 4000K **IP54**

OL9611 / OL9612

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9611LEDW1	C	3	210	4000-4300	dark grey	153	72.6	106.4	1/16	A++→A
9611LEDW2	C	2X3W	320	4000-4300	dark grey	231.6	72.6	106.4	1/16	A++→A
9612LEDW1	C	3	210	4000-4300	dark grey	170	92	65	1/12	A++→A
9612LEDW2	C	2X3W	320	4000-4300	dark grey	200	92	65	1/12	A++→A



Body: aluminium | **Diffuser:** tempered glass | **LED driver:** mounted in the body | **Light source:** CREE LED
Operating temperature: -20°C÷+65°C

~230V 50/60 Hz Ra>80 >15000 INSTANT 100% 30000h Hg IP 54 RoHS COMPLIANT EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR LED WALL LIGHTS WITH SENSOR
98SOL200

SOLAR LED WALL LIGHTS WITH SENSOR
98SOL201

LED IP54 Solar

SOLAR LED WALL LIGHTS WITH SENSOR

Catalogue number	Product category	LED QTY	Power (W)	Whole fixtures lumens (lm)	Solar panel (Wp)	Sensor range (m)	Colour of body	Length (mm)	Height (mm)	Width (mm)	Packing/ Box (pcs)	Energy class
98SOL200	C	14 (FRONT 14+BACK 2PCS)	7	200	0.7- POLY CRISTALLINE	6	white	144.5	96	79	1	A++→A
98SOL201	C	17 (FRONT 16+BACK 1PCS)	10	240	0.7- POLY CRISTALLINE	6	white	200	105	90	1	A++→A

Material: ABS + PC, anti UV and glossy | **LED&Lens:** LM-80 LEDs 2835SMD; high transmittance PC optical lens | Detection angle: 120° | **Installation height:** ≤ 4meters | **Battery:** 3.7V/ 1200mAh

98SOL200 Auto on at night; Full brightnessby motion activated. Weak brightness when no motion | **Time delay:** 10 sek | **Modes:** A- Full brightness+Weak brightness (front and back lights ON); B- Full brightness+Weak brightness (front light OFF, back lights ON) | Auto on at night; Full brightnes

98SOL201 Auto on at night; Full brightnessby motion activated. Weak brightness when no motion | **Time delay:** 10 sek | Battery >30%: Full brightness+Weak brightness (front and back lights ON); Battery<30%: Full brightness+Weak brightness (front light OFF, back lights ON) | Auto on at night; Full brightnes

98SOL200

98SOL201



SMD 30000h IP 54 RoHS CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR FIXTURE SOL WITH SENSOR
98SOL300

SOLAR FIXTURE SOL WITH SENSOR
98SOL302

SOLAR FIXTURE SOL WITH SENSOR
98SOL301

LED IP65 Solar

SOLAR LED FLOOD LIGHT WITH SENSOR

Catalogue number	Product category	LED QTY	Power (W)	Whole fixture lumens (lm)	Battery (V/mAh)	Sensor range (m)	Colour body	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
98SOL300	C	30	30	500	3.7V/ 2X1500mAh	6	black	217.4	149.3	33.7	1	A++→A
98SOL301	C	72	50	1080	3.7V/7200mAh	6	black	300	215	35	1	A++→A
98SOL302	C	55	50	1100	3.7V/ 7200mAh	6	black	-	165	35	1	A++→A

Material: ABS + PC, anti UV and glossy | **3working mode** | **98SOL302:** Portable solar panel.Can use as portable power bank

SMD RoHS CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



SOLAR LED FLOOD LIGHTS
98SOL303

SOLAR LED FLOOD LIGHTS
98SOL304

LED **IP54** **IP65** **Solar**

SOLAR LED FLOOD LIGHTS

Catalogue number	Product category	Solar panel	Power (W)	Whole fixtures lumens (lm)	Battery (V/mAh)	Colour body	Length (mm)	Height (mm)	Width (mm)	Packing/ Box (pcs)	Energy class
98SOL303	C	5V/25W	100	1100	3.6V/15000MAH	white	188	168	42	1/8	A++→A
98SOL304	C	5V/35W	200	2000	3.6V/25000MAH	white	253	220	45	1/4	A++→A

Material: Alu | **Working mode:** Light+PIR induction | **Charging time:** 5-8hrs | **Working time:** 10-12hrs | **Light source:** LED SMD 5730 | **Beam angle:** 110° | **Solar panel type:** poly cristalline | **Solar panel:** IP65 | **Solar floodlight:** IP54

SMD 30000h Hg IP 54 IP 65 RoHS CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GRF
96GRF190B/AB

IP68

UNTIL SUPPLY LAST

GRF

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Height (mm)	Lampholder	Material	Packing/Box (pcs)	Energy class
96GRF190B/AB	F	Ground recessed fixtures	Antique bronze	98	190	1 x GU5.3	Composite material	1/12	A++→E

Lamps not included. The fixtures are with 6m cable.

12V 50/60 Hz MR-16 GU5.3 1,5mm² IP68 RoHS III F CE 3+0 standard +extended 3 YEAR TOTAL WARRANTY

UNDERWATER LED
98LED012SW

UNDERWATER LED
98LED007SW

UNDERWATER LED
98LED003SW

LED **IP68**

UNDERWATER LED LIGHTS, IP68

Catalogue number	Product category	Voltage (V)	Watt (W)	Whole lamp lumens (lm)	Colour temp. (K)	Colour body	Packing/Box (pcs)	Energy class
98LED003SW	C	12V AC	3 X 1	150	4000	silver	1/30	A++→A
98LED007SW	C	12V AC	7 X 1	350	4000	silver	1/1	A++→A
98LED012SW	C	24V AC	12 X 1	600	4000	silver	1/1	A++→A
98LED006RGB	C	12V AC	6 X 1	-	RGB	silver	1/1	A++→A



Body: Stainless steel | **Light source:** Epistar | **Beam angle:** 90° | **without driver**

Ra>70 IP68 >15000 INSTANT 100% 20000h RoHS COMPLIANT F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MINI TOMMY ELSP
96TOMMYELSP/BL

MINI TOMMY EL
96TOMMYEL/BL

IP66 **Resin**

UNTIL SUPPLY LAST

MINI TOMMY EL / MINI TOMMY ELSP

Catalogue number	Product category	Description	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour	Diameter (mm)	Width (mm)	Height (mm)	Lampholder	Packing/ Box (pcs)	Energy class
96TOMMYEL/BL	F	Ground/Wall fixture	6	600	2700/4000K settable	black	122	118	127	1xGU10	1/30	A+ A++→A
96TOMMYEL/GR	F	Ground/Wall fixture	6	600	2700/4000K settable	gray	122	118	127	1xGU10	1/30	A+ A++→A
96TOMMYELSP/BL	F	Spike ground fixture	6	600	2700/4000K settable	black	122	118	310	1xGU10	1/30	A+ A++→A
96TOMMYELSP/GR	F	Spike ground fixture	6	600	2700/4000K settable	gray	122	118	310	1xGU10	1/30	A+ A++→A

Body material: Resin | **UV resistant** | **Lamp not included** | **Fully adjustable position** | **Lamp holder:** GU10

The product is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99LED729 GU 10 LED SMD 6.5W 4000K | **99LED730** GU 10 LED SMD 6.5W 2700K | **99LED796** GU 10 LED SMD 6.5W 6400K
99LED733 GU 10 LED SMD RED | **99LED734** GU 10 LED SMD BLUE | **99LED735** GU 10 LED SMD GREEN

~230V | 50/60 Hz | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

GARDEN FIXTURES GRF317
96GRF317/BL

GARDEN FIXTURES GRF317
96GRF317/GR

GARDEN FIXTURES GRF316
96GRF316/BL

GARDEN FIXTURES GRF316
96GRF316/GR

IP54

GARDEN FIXTURES GRF316 AND GRF317

Catalogue number BLACK	Catalogue number GREY	Product category	Description	Diameter (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF316/BL	**96GRF316/GR**	C	Spike ground fixture	86	235	155	1XGU10	1/20	A++→E
96GRF317/BL	**96GRF317/GR**	C	Ground/Wall fixture	86	73	155	1XGU10	1/20	A++→E

Material: UV resistant ABS+ PC | **Spoke length:** 162mm| **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

GARDEN FIXTURES GRF318
96GRF318/BL

GARDEN FIXTURES GRF318
96GRF318/GR

GARDEN FIXTURES GRF319
96GRF319/BL

GARDEN FIXTURES GRF319
96GRF319/GR

IP54

GARDEN FIXTURES GRF318 AND GRF319

Catalogue number BLACK	Catalogue number GREY	Product category	Description	Diameter (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF319/BL	**96GRF319/GR**	C	Spike ground fixture	98	224	100	1XGU10	1/20	A++→E
96GRF318/BL	**96GRF318/GR**	C	Ground/Wall fixture	98	162	100	1XGU10	1/20	A++→E

Material: UV resistant ABS+ PC | **Spoke length:** 162mm| **Input voltage:** 220-240VAC | **Mounting:** Surface | **Lamp:** Not included

~230V | 50/60 Hz | RoHS COMPLIANT | 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

GRF 9615 LED
9615LEDP

GRF 9616 LED
9616LEDW

GRF 9617 LED
9617LEDP

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP65**

GRF 9615 / 9616 / 9617

Catalogue number	Product category	Watt (W)	Body	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9615LEDP	C	3	aluminium	210	4000-4300	dark grey	279	73	112	1/16	A++→A
9616LEDW	C	3	aluminium	210	4000-4300	dark grey		73	110	1/16	A++→A
9617LEDP	C	5	PP+PC	360	5500-6000	dark grey	265	25	130	1/16	A++→A

Diffuser: tempered glass | **LED driver:** mounted in the body | **Operating temperature:** -20°C÷+65°C

Terminal box IP44

Material: PC
Voltage: 450V
Rated current: 6A
Wiring Capacity: 0.5-4.0mm2

Cat. Number: 31071

Terminal box IP65

Material: Polypropylene 94-V2 grade
Sunscreen Rating:Sun Protection(UV)
Voltage: 450V
Rated current: 10A
Terminal Blocks: 3p screw type
Metal Part:Plated Brass/Steel Spring
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31070

Cable connector IP68

Rated operational voltage:AC250V
Rated operational Ampere(A):≤30A
Material: flame retardant/Anti UV nylon(PA66)
Crimping terminals:Nickle-plated brass
Withstand voltage(normal temperature):3KV
Operating remperature range: -40°C~+105°C
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31072

~230V | 50/60 Hz | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GRF
96GRF187/CU

GRF
96GRF457LSP/AB

GRF
96GRF76B/AB

GRF
96GRF70B/AB

IP65

UNTIL SUPPLY LAST

GRF

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Height (mm)	Lampholder	Material	Packing/Box (pcs)	Energy class
96GRF187/CU	F	Ground recessed fixtures	Copper	54	187	1 x GU10	Copper	1/12	A++→E

~230V | 50/60 Hz | IP 65 | RoHS | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

UNTIL SUPPLY LAST

GRF

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Height (mm)	Material	Packing/Box (pcs)
96GRF70B/AB	F	Connector for wall recessed fixtures	Antique bronze	70	28	Brass	1/50
96GRF76B/AB	F	connector for pole D50-70 mm	Antique bronze	76	73	Brass	1/60
96GRF457LSP/AB	F	riser type for ground recessed fixtures	Antique bronze	25	457	Brass	1/30

SOLAR TORCH LIGHT

98SOL96

LED | WARM WHITE 2700K | IP54 | Solar

SOLAR TORCH LIGHT

Catalogue number	Product category	LED qty	Power (W)	Colour temp. (K)	Whole fixture lumens (lm)	Solar panel (V/mA)	Battery (V/mAh)	Colour body	Diameter (mm)	Length (mm)	Packing/Box (pcs)	Energy class
98SOL96	C	51	max 1W	1500-1800	20	5.5V/0.66W	3.7V/1200mAh	black	120	770	1/10	A++→A

Material: ABS+PC | **Charge time (h):** 8h | **Working Time:** 8h | **Light souce:** 2835 | **Mode:** Dark On>Off | **Beam angle:** 360° | **Battery:** Included

RoHS COMPLIANT | CE | 1+0 standard +extended | 1 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR GROUND LIGHT
98SOL5420

SOLAR GROUND LIGHT
98SOL5520

SOLAR GROUND LIGHT
98SOL9620

SOLAR GROUND LIGHT
98SOL23310

LED IP44 Solar

SOLAR GROUND LIGHT

Catalogue number	Product category	Power (W)	Whole fixture lumens (lm)	Solar panel	Battery (V/mAh)	Working time	Material	Colour body	Length (mm)	Diameter (mm)	Packing/Box (pcs)	Energy class
98SOL5420	C	0,06	1	amorphous	Ni-Mh/100mAh AA 1.2V	8h	plastic	black	370	75/75	1/12	A++→A
98SOL5520	C	0,06	1	amorphous	Ni-Mh/100mAh AAA 1.2V	8h	plastic	black	365	85/85	9/8	A++→A
98SOL9620	C	0,06	1	amorphous	Ni-Mh/100mAh AAA 1.2V	8h	plastic	black	380	64	1/24	A++→A
98SOL23310	C	0.08	2	amorphous	Ni-Mh AAA 2V	8h	plastic	black	373	57/57	1/24	A++→A

RoHS COMPLIANT CE 1+0 standard +extended 1 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR GROUND LIGHT
98SOL4320

SOLAR GROUND LIGHT
98SOL8120

SOLAR GROUND LIGHT
98SOL5821

LED IP44 Solar

SOLAR GROUND LIGHT

Catalogue number	Product category	Power (W)	Whole fixture lumens (lm)	Solar panel	Battery (V/mAh)	Working time	Material	Colour body	Length (mm)	Diameter (mm)	Packing/Box (pcs)	Energy class
98SOL4320	C	0,5	15	polycrystal	NI-MH AA 300mAh 1.2V	8h	plastic	black	425	130/110	1/12	A++→A
8SOL23276	C	0,4	25	polycristal	14430 LiFePO4 400mAh	8h	plastic	black	260	69	1/24	A++→A
98SOL8120	C	0,06	1	amorphous	Ni-Mh/40mAh button battery 1.2V	8h	plastic	black	340	100	1/16	A++→A
98SOL5821	C	0,24	4	amorphous	Ni-Mh/200mAh AA 1.2V	8h	plastic	silver	510	200	1/8	A++→A

RoHS COMPLIANT CE 1+0 standard +extended 1 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR GROUND LIGHT
98SOL6721



SOLAR GROUND LIGHT
98SOL3122

SOLAR GROUND LIGHT
98SOL6921

LED IP44 Solar Metal

SOLAR GROUND LIGHT

Catalogue number	Product category	Power (W)	Whole fixture lumens (lm)	Solar panel	Battery (V/mAh)	Working time	Material	Colour body	Length (mm)	Diameter (mm)	Packing/Box (pcs)	Energy class
98SOL3122	C	0,06	1	amorphous	Ni-Mh/100mAh AAA 1.2V	8h	stainless steel+plastic	brass	390	85	4/12	A++→A
98SOL6721	C	0,06	1	amorphous	Ni-Mh/200mAh AA 1.2V	8h	stainless steel+plastic	silver	370	128	1/6	A++→A
98SOL6921	C	0,06	1	amorphous	Ni-Mh/100mAh AAA 1.2V	8h	stainless steel + plastic	black	355	72	1/12	A++→A

RoHS COMPLIANT CE 1+0 standard +extended 1 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR GROUND LIGHT
98SOL11103

SOLAR GROUND LIGHT
98SOL11088

LED IP44 Solar

SOLAR GROUND LIGHT

Catalogue number	Product category	Power (W)	Whole fixture lumens (lm)	Solar panel	Battery (V/mAh)	Working time	Material	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98SOL11103	C	0.16	8	poly	Ni-Mh/400mAh	8h	Steinless steel	Grey	59	59	281.5	1/24	A++→A
98SOL11088	C	0.3	10	poly	Ni-Mh/900mAh	8h	Steinless steel	Grey	120	120	420	1/24	A++→A

RoHS CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR WALL LIGHT
98SOL23357W

SOLAR PATHWAY LIGHT
98SOL23357

LED IP44 Solar

SOLAR PATHWAY & WALL LIGHTS

Catalogue number	Product category	Power (W)	Whole fixture lumens (lm)	Solar panel	Battery (V/mAh)	Working time	Material	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98SOL23357	C	0.2	10	poly	Ni-Mh/500mAh	8h	Plastic	Black	108	108	405	1/24	A++→A
98SOL23357W	C	0.2	10	poly	Ni-Mh/500mAh	8h	Plastic	Black	108	108	202.5	1/24	A++→A

RoHS CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

DRIVEWAY LIGHTS
98SOL41029

DRIVEWAY LIGHTS
98SOL41071

LED IP44 Solar Metal

SOLAR DRIVEWAY LIGHTS

Catalogue number	Product category	Power (W)	Whole fixture lumens (lm)	Solar panel	Battery (V/mAh)	Working time	Material	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98SOL41029	C	0,24	6	poly	Ni-Mh/ 600mAh	8h	aluminium	grey	69	100	26	1/24	A++→A
98SOL41071	C	0.3	10	poly	Ni-Mh/900mAh	8h	aluminium	grey	136	136	30	1/24	A++→A

RoHS COMPLIANT CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



SOLAR WALL
98SOL23428

SOLAR WALL
98SOL23423

SOLAR WALL
98SOL23429

LED IP44 Solar

SOLAR WALL LIGHTS

Catalogue number	Product category	Power (W)	Whole fixture lumens (lm)	Solar panel	Battery (V/mAh)	Working time	Material	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98SOL23423	C	0,8	30	mono	LiFePO4/800mAh 18500 4.5V	8h	plastic	black	100	100	100	1/24	A++→A
98SOL23428	C	0,3	10	mono	Ni-Mh/ 900mAh 2V	8h	plastic	black	145	145	55	1/24	A++→A
98SOL23429	C	0,12	6	amorphous	Ni-Mh/ 300mAh 2V	8h	plastic	black	90		73	1/24	A++→A

RoHS CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR STRING LIGHTS
98SOL23439

SOLAR STRING LIGHTS
98SOL23451

LED **IP68** **Solar**

SOLAR STRING LIGHTS

Catalogue number	Product category	Fixtures QTY	Power (W)	Whole fixture lumens (lm)	Light colour	Solar panel	Battery (V/mAh)	Working time	Material	Cable length (mm)	Packing/Box (pcs)	Energy class
98SOL23439	C	8	0.6	24	warm	poly	2x Ni-Mh/900mAh	8h	Plastic	3000	1/24	A++→A
98SOL23451	C	8	0.6	24	warm	poly	2x Ni-Mh/900mAh	8h	Plastic	4300	1/24	A++→A

RoHS COMPLIANT CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR CRISTMAS/ GARDEN LIGHTS

98SOL23204C

LED IP44 Solar

SOLAR CRISTMAS/GARDEN LIGHTS

Catalogue number	Product category	Lights QTY	Power (W)	Light colour	Solar panel	Battery (V/mAh)	Working time	Material	Cable length (mm)	Packing/Box (pcs)	Energy class
98SOL23204C	C	100	0.5	RGBY	poly	Ni-Mh/1200mAh	8h	Plastic	13	1/24	A++→A

4 strings of 25pcs red, yellow, green, blue LEDs

RoHS COMPLIANT CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

CECI 90 SQUARE
96CECI90SQ/GR

CECI 90 SQUARE
96CECI90SQ/BL

LED | 3000 K 4000 K | IP67 | DRIVE OVER

CECI 90 SQUARE

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length/ Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96CECI90SQ/BL	C	6	600	2700/4000 settable	BLACK	90/92	127	1/40	A+ A++→A
96CECI90SQ/GR	C	6	600	2700/4000 settable	GREY	90/92	127	1/40	A+ A++→A

Body: Resin with frosted diffuser | **UV resistant** | Drive-over | **Lamp holder:** GU10 | Lamp included

50/60 Hz | IP 67 | RoHS | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of 96GRFLED068 the delivery time after order confirmation will be 90 days, and for others products 45 days.

CECI 160 ROUND
96CECI160/GR

CECI 160 ROUND
96CECI160/BL

LED | 3000 K 4000 K 6000 K | IP67 | DRIVE OVER

CECI 160 ROUND

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
96CECI160/BL	C	10	1200	2700/4000/6500 settable	BLACK	160	111	1/18	A+ A++→A
96CECI160/GR	C	10	1200	2700/4000/6500 settable	GREY	160	111	1/18	A+ A++→A

Body: Resin with frosted diffuser | **UV resistant** | Drive-over | **Lamp holder:** GX53 | Lamp included

50/60 Hz | IP 67 | RoHS COMPLIANT | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of 96GRFLED068 the delivery time after order confirmation will be 90 days, and for others products 45 days.

ALDO 2L
96ALDO2L/BL

ALDO
96ALDO/GR

LED | NEUTRAL WHITE 4000K | IP67 | DRIVE OVER | Resin

ALDO

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Diameter 1 (mm)	Beam angle	Packing/Box (pcs)	Energy class
96ALDO/BL	C	ALDO	1.7	170	4000	Black	50	47	110	1/50	A+ A++→A
96ALDO/GR	C	ALDO	1.7	170	4000	Grey	50	47	110	1/50	A+ A++→A
96ALDO2L/BL	C	ALDO 2L	1.7	170	4000	Black	50	47	110	1/50	A+ A++→A
96ALDO2L/GR	C	ALDO 2L	1.7	170	4000	Grey	50	47	110	1/50	A+ A++→A

Body: Resin with opal glass | **UV resistant** | **Lamp holder:** G9 | **Lamp included**

The product ALDO is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99LED933 G9 LED 7W 3000K | **99LED933W** G9 LED 7W 4000K | **99LED933CW** G9 LED 7W 6400K

50/60 Hz | IP 67 | RoHS | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of 96GRFLED068 the delivery time after order confirmation will be 90 days, and for others products 45 days.

CECI 90 3L
96CECI3L/BL

CECI 90
96CECI90/GR

GRF
96GRFLED068

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | IP67 | DRIVE OVER

GRF068 / CECI 90 ROUND

Catalogue number	Product category	Model	Colour	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
96CECI90/BL	C	CECI 90	Black	3.5	400	2700/4000K settable	95	127	45°	1/40	A+ A++→A
96CECI90/GR	C	CECI 90	Gray	3.5	400	2700/4000K settable	95	127	45°	1/40	A+ A++→A
96CECI3L/BL	C	CECI 90 3L	Black	3.5	400	2700/4000K settable	95	127	45°	1/40	A+ A++→A
96CECI3L/GR	C	CECI 90 3L	Gray	3.5	400	2700/4000K settable	95	127	45°	1/40	A+ A++→A
96GRFLED068	C	GRF	Gray	1	60	6000-6500	100	61	45°	1/40	A++→A

GRF067: Material: 304 Stainless steel | **Voltage:** 100-240V | **LED** source: Integrated SMD Epistar | IK10 | Corrosion proof
CECI: Material: Resin | UV resistant | Lamp included | **Lamp holder:** GU10

The product CECI 90 and CECI 90 3L are accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99LED729 GU 10 LED SMD 6.5W 4000K | **99LED730** GU 10 LED SMD 6.5W 2700K | **99LED796** GU 10 LED SMD 6.5W 6400K

99LED733 GU 10 LED SMD RED | **99LED734** GU 10 LED SMD BLUE | **99LED735** GU 10 LED SMD GREEN

50/60 Hz | IP 67 | RoHS | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of 96GRFLED068 the delivery time after order confirmation will be 90 days, and for others products 45 days.

GRF109 IP67

IP67

UNTIL SUPPLY LAST

EMPTY FIXTURE GRF 109, IP67

Catalogue number	Product category	Watt (W)	Voltage (V)	Lamp	Colour	Current (A)	Balast	Diameter (mm)	Length (mm)	Height (mm)	Energy class
96GRF109/150	F		230	MHL	satin nickel		empty	260	280	185	A++→E

Body: PVC | **Diffuser:** aluminium ring and tempered glass | Lamp not included
Load capacity is 3 ton. | w/o driver

~230V | IP 67 | RoHS COMPLIANT | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

GRF105 IP65
96GRF105

GRF106 IP65
96GRF106

IP65

EMPTY FIXTURE GRF, IP65

Catalogue number	Product category	Watt (W)	Voltage (V)	Lamp holder	Colour	Diameter (mm)	Length (mm)	Packing/Box (pcs)	Energy class
96GRF105	C	max.50W	12	1 x GU5.3	satin nickel	107	145	1/20	A++→A
96GRF106	C	max.50W	220	1 x GU10	satin nickel	107	145	1/20	A++→A

Body: PVC | **Diffuser:** aluminium ring and tempered glass | Lamp not included
Load capacity is 3 ton. | w/o driver

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

RAY
96RAY40

RAY
96RAY30

RAY
96RAY20

RAY
96RAY10

LED COOL WHITE 6400K **IP67**

RAY

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour aluminium ring	Diameter (mm)	Diameter 1 (mm)	Length (mm)	Packing/Box (pcs)	Energy class
96RAY10	C	13	1000	5500	satin nickel	160	150	100	1/12	A++→A
96RAY20	C	20	1800	5500	satin nickel	180	160	123	1/8	A++→A
96RAY30	C	30	2700	5500	satin nickel	230	210	135	1/6	A++→A
96RAY40	C	40	3600	5500	satin nickel	230	215	135	1/6	A++→A

Body: aluminium | **Diffuser:** aluminium ring and tempered glass | Load capacity is 2.5 ton | **LED driver:** mounted in the body
Light source: Epistar LED

~230V 50/60 Hz Ra>80 >15000 INSTANT 100% 30000h Hg IP 67 RoHS COMPLIANT EMC F CE 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

WADE FIXTURE IP65

LED COOL WHITE 6400K **IP65**

WADE FIXTURE IP65

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9WF18CW	C	18	1600	6500	white	700	55	35	1/20	A++→A
9WF36CW	C	36	3500	6500	white	1230	55	35	1/12	A++→A
9WF45CW	C	45	4300	6500	white	1530	53	35	1/12	A++→A

Body: polycarbonate (PC) | **Diffuser:** polycarbonate (PC) | **Clamps:** inox | **Light source:** Sanan 2835 SMD| **Power factor:** λ>0.9 | **Starting time:** <1s | **Beam angle:** 120°
Cable gland, metal clips for wall fixing.

~230V | 50/60 Hz | SMD | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | CE | 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

BELLA STELLAR SMD2835

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP65**

BELLA STELLAR SMD2835

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9XBR18LED	C	18	1620	4000	Grey	610	75	62	1/8	A++→A
9XBR18LEDCW	C	18	1620	6500	Grey	610	75	62	1/8	A++→A
9XBR36LED	C	36	3240	4000	Grey	1210	75	62	1/8	A++→A
9XBR36LEDCW	C	36	3240	6500	Grey	1210	75	62	1/8	A++→A
9XBR54LED	C	54	4860	4000	Grey	1510	75	62	1/8	A++→A
9XBR54LEDCW	C	54	4860	6500	Grey	1510	75	62	1/8	A++→A

Body: PC | **Diffuser:** PC Opal | **Clips:** polycarbonate | **Cable gland, metal clips for wall fixing** | **Light source:** Sanan 2835SMD

~230V | 50/60 Hz | SMD | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

BELLA SMD2835

LED NEUTRAL WHITE 4000K COOL WHITE 6400K **IP65**

BELLA LUMINAIRE SMD2835

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9BR20LED	-	C	20	1800	4000	grey	600	80	70	1/16	A++→A
9BR20LEDCW	-	C	20	1800	6500	grey	600	80	70	1/16	A++→A
9BR40LED	**9BR40LEDE**	C	40	3800	4000	grey	1200	80	70	1/12	A++→A
9BR40LEDCW	**9BR40LEDCWE**	C	40	3800	6500	grey	1200	80	70	1/12	A++→A
9BR55LED	**9BR55LEDE**	C	55	5000	4000	grey	1476	80	70	1/9	A++→A
9BR55LEDCW	**9BR55LEDCWE**	C	55	5000	6500	grey	1476	80	70	1/9	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: polycarbonate (PC), grey | **Diffuser:** polycarbonate (PC), Opal cover | **Reflector:** steel white | **Light source:** Epistar | Cable gland.

~230V | 50/60 Hz | SMD | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | CE | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

BELLA with LED Tubes T8 STELLAR

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP65**

BELLA with LED Tubes T8 STELLAR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9BR109LEDCW	C	1X9	585	6200-6500	grey	655	68	58	1/8	A+ A++→A
9BR109LED	C	1X9	585	4000-4300	grey	655	68	58	1/8	A+ A++→A
9BR209LEDCW	C	2X9	1170	6200-6500	grey	655	113	58	1/6	A+ A++→A
9BR209LED	C	2X9	1170	4000-4300	grey	655	113	58	1/6	A+ A++→A
9BR118LEDCW	C	1X18	1170	6200-6500	grey	1270	68	58	1/8	A+ A++→A
9BR118LED	C	1X18	1170	4000-4300	grey	1270	68	58	1/8	A+ A++→A
9BR218LEDCW	C	2X18	2340	6200-6500	grey	1270	113	58	1/8	A+ A++→A
9BR218LED	C	2X18	2340	4000-4300	grey	1270	113	58	1/8	A+ A++→A
9BR122LEDCW	C	1X24	1430	6200-6500	grey	1565	68	58	1/8	A+ A++→A
9BR122LED	C	1X24	1430	4000-4300	grey	1565	68	58	1/8	A+ A++→A
9BR222LEDCW	C	2X24	2860	6200-6500	grey	1565	113	58	1/6	A+ A++→A
9BR222LED	C	2X24	2860	4000-4300	grey	1565	113	58	1/6	A+ A++→A

with LED tubes STELLAR

Body: ABC | **Diffuser:** polycarbonate (PC) | **Reflector:** without | **Clips:** polycarbonate | Cable gland, metal clips for wall fixing. | **Light source:** LED tubes

~230V | 50/60 Hz | LED T8 | G13 | Ra≥80 | >10000 | INSTANT 100% | 15000h | Hg | IP 65 | RoHS COMPLIANT | EMC | 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED NEUTRAL WHITE 4000K COOL WHITE 6400K **IP65**

BELLA with LED Tubes T8 ELMARK

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9BM110LEDCW	-	C	1X10	800	6500	grey	670	86	100	1/12	A+ A++→A
9BM110LED	-	C	1X10	800	4000	grey	670	86	100	1/12	A+ A++→A
9BM118LEDCW	-	C	1X18	1440	6500	grey	1270	86	100	1/9	A+ A++→A
9BM118LED	-	C	1X18	1440	4000	grey	1270	86	100	1/9	A+ A++→A
9BM124LEDCW	-	C	1X24	1920	6500	grey	1570	106	110	1/6	A+ A++→A
9BM124LED	-	C	1X24	1920	4000	grey	1570	106	110	1/6	A+ A++→A
9BM210LEDCW	-	C	2X10	1600	6500	grey	670	131	100	1/9	A+ A++→A
9BM210LED	-	C	2X10	1600	4000	grey	670	131	100	1/9	A+ A++→A
9BM218LEDCW	**9BM218LEDCWE**	C	2X18	2880	6500	grey	1270	131	100	1/6	A+ A++→A
9BM218LED	**9BM218LEDE**	C	2X18	2880	4000	grey	1270	131	100	1/6	A+ A++→A
9BM224LEDCW	**9BM224LEDCWE**	C	2X24	3840	6500	grey	1570	166	110	1/4	A+ A++→A
9BM224LED	**9BM224LEDE**	C	2X24	3840	4000	grey	1570	166	110	1/4	A+ A++→A

with LED tubes ELMARK

We offer the fixtures as per personal request with a fixed block and battery with a possibility for work in an emergency regime 60-180min

Wire and fittings for hanging mounting 2,5m
2 pcs/ pack
92ACC03

Body: polycarbonate (PC) | **Diffuser:** polycarbonate (PC) | **Reflector:** steel white | Ballast: fixed inside the body | **Clamps:** polycarbonate | Cable gland, metal clips for wall fixing.

~230V | 50/60 Hz | LED T8 | G13 | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP65**

UNTIL SUPPLY **LAST**

BELLA luminaire with LED tubes T5 ELMARK

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9BE114LEDW	F	1X10	1000	4000	grey	670	74	80	1/12	A+ A++→A
9BE128LEDW	F	1X20	2000	4000	grey	1210	64	85	1/9	A+ A++→A
9BE214LEDW	F	2X10	2000	4000	grey	670	106	80	1/9	A+ A++→A
9BE114LEDCW	F	1X10	1000	6400	grey	670	74	80	1/12	A+ A++→A
9BE128LEDCW	F	1X20	2000	6400	grey	1210	64	85	1/9	A+ A++→A
9BE214LEDCW	F	2X10	2000	6400	grey	670	106	80	1/9	A+ A++→A

with LED tubes ELMARK

Body: polycarbonate (PC) | **Diffuser:** polycarbonate (PC) | **Reflector:** steel white | **Clamps:** inox | Cable gland, metal clips for wall fixing.

~230V | 50/60 Hz | LED T5 | G5 | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

IP65

EMPTY FIXTURES BELLA FOR SINGLE ENDED LED TUBES T8

Catalogue number	Variant	Product category	Led tube size	Colour	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
89084	Slim	C	1x600mm	grey	670	86	100	1/12	A++→B
89085	Slim	C	2x600mm	grey	670	131	100	1/9	A++→B
89086	Slim	C	1x1200mm	grey	1270	86	100	1/9	A++→B
89087	Slim	C	2x1200mm	grey	1270	131	100	1/6	A++→B
89088	Slim	C	1x1500mm	grey	1570	86	100	1/6	A++→B
89089	Slim	C	2x1500mm	grey	1570	131	100	1/4	A++→B

Body: polycarbonate (PC) | **Diffuser:** polycarbonate (PC) | **Reflector:** steel white | **Clips:** polycarbonate | Cable gland, metal clips for wall fixing. | Lamp not included

~230V | 50/60 Hz | G13 | IP 65 | RoHS COMPLIANT | EMC | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

GERMANA
95GERMANA/BL

GERMANA
95GERMANA/GR

GERMANA G
95GERMANAG/BL

GERMANA G
95GERMANAG/GR

IP66 **Resin**

GERMANA

Catalogue number	Product category	Colour body	Lampholder	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95GERMANA/BL	F*	Black	1xE27	180	160	250	1/18	A++→C
95GERMANA/GR	F*	Grey	1xE27	180	160	250	1/18	A++→C
95GERMANAG/BL	C	Black	1xE27	180	300	250	1/18	A++→C
95GERMANAG/GR	C	Grey	1xE27	180	300	250	1/18	A++→C

Body: Resin with opal diffuser | **UV resistant** | **Lamp holder:** E27 | **Lamp not included**

*Until Supply last

Recommended bulbs:
99LED588 LED PEAR A60 12W 4000K |
99LED587 LED PEAR A60 12W 2700K |
99LED821 LED PEAR A60 12W 6400K

~230V | 50/60 Hz | E27 | RoHS | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

WALL LAMP GRF312
96GRF312/BL

WALL LAMP GRF312
96GRF312/GR

IP65

WALL LAMP GRF312

Catalogue number	Product category	Description	Colour body	Length (mm)	Height (mm)	Width (mm)	Lampholder	Packing/Box (pcs)	Energy class
96GRF312/BL	C	Wall lamp	Black	320	139	138	2XE27	1/10	1/10
96GRF312/GR	C	Wall lamp	Grey	320	139	138	2XE27	1/10	1/10

Material: UV resistant ABS+ PC | **Input voltage:** 220-240VAC | **Mounting:** Surface| **Lamp:** Not included

~230V 50/60 Hz RoHS COMPLIANT F CE 2+1 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 45 days.

LED COOL WHITE 6400K **IP65**

HELIOS SMD

Catalogue number	Catalogue number with Emergency kit	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98HELIOS10	-	C	HELIOS10	10	800	5000-5500	black	105	25	85	1/40	A++→A
98HELIOS20	-	C	HELIOS20	20	1600	5000-5500	black	128	25	88	1/40	A++→A
98HELIOS30	**98HELIOS30E**	C	HELIOS30	30	2400	5000-5500	black	153	25	111	1/20	A++→A
98HELIOS50	**98HELIOS50E**	C	HELIOS50	50	4000	5000-5500	black	205	30	160	1/20	A++→A
98HELIOS100	**98HELIOS100E**	C	HELIOS100	100	8000	5000-5500	black	300	30	205	1/10	A++→A
98HELIOS150	-	C	HELIOS150	150	10000	5000-5500	black	333	40	254	1/10	A++→A
98HELIOS200	-	C	HELIOS200	200	12000	5000-5500	black	360	42	280	1/10	A++→A
98HELIOS20SEN	-	C	HELIOS20SEN	20	1600	5000-5500	black	134	35	109	1/20	A++→A
98HELIOS30SEN	**98HELIOS30SENE**	C	HELIOS30SEN	30	2400	5000-5500	black	173	35	136	1/10	A++→A
98HELIOS50SEN	**98HELIOS50SENE**	C	HELIOS50SEN	50	4000	5000-5500	black	210	35	163	1/10	A++→A

Body: Aluminium casting | **LED driver:** mounted in the body | **Light source:** Epistar SMD2835 | **Input voltage:** 176 - 264V | **Ambient Temperature:** -20°C÷ +55°C
Sensor: detection range:120° | **Detection distance:** MAX 8 m(±2 m) | **Time setting:** 140±20 s | **Ambient light:** 25±10 lux

Terminal box IP44

Material: PC
Voltage: 450V
Rated current: 6A
Wiring Capacity: 0.5-4.0mm2
Cat. Number: 31071

Terminal box IP65

Material: Polypropylene 94-V2 grade
Sunscreen Rating:Sun Protection(UV)
Voltage: 450V
Rated current: 10A
Terminal Blocks: 3p screw type
Metal Part:Plated Brass/Steel Spring
Wiring Capacity: 0.5-2.5mm2
Cat. Number: 31070

Cable connector IP68

Rated operational voltage:AC250V
Rated operational Ampere(A):≤30A
Material: flame retardant/Anti UV nylon(PA66)
Crimping terminals:Nickle-plated brass
Withstand voltage(normal temperature):3KV
Operating remperature range: -40°C~+105°C
Wiring Capacity: 0.5-2.5mm2
Cat. Number: 31072

~230V | 50/60 Hz | 120° | Ra>70 | 15000h | Hg | IP 65 | RoHS COMPLIANT | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED NEUTRAL WHITE 4000K **IP65**

HELIOS SMD

Catalogue number	Catalogue number with Emergency kit	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98HELIOS10/WH	-	C	HELIOS10	10	800	4000	white	105	25	85	1/50	A++⇨A
98HELIOS20/WH	-	C	HELIOS20	20	1600	4000	white	128	25	88	1/50	A++⇨A
98HELIOS30/WH	**98HELIOS30/WHE**	C	HELIOS30	30	2400	4000	white	153	25	111	1/30	A++⇨A
98HELIOS50/WH	**98HELIOS50/WHE**	C	HELIOS50	50	4000	4000	white	205	30	160	1/20	A++⇨A
98HELIOS100/WH	**98HELIOS100/WHE**	C	HELIOS100	100	8000	4000	white	300	30	205	1/10	A++⇨A

Body: Aluminium casting | **LED driver:** mounted in the body | **Light source:** Epistar SMD2835 | **Input voltage:** 176 - 264V | **Ambient Temperature:** -20°C÷ +55°C

Side View

Terminal box IP44

Material: PC
Voltage: 450V
Rated current: 6A
Wiring Capacity: 0.5-4.0mm2

Cat. Number: 31071

Terminal box IP65

Material: Polypropylene 94-V2 grade
Sunscreen Rating:Sun Protection(UV)
Voltage: 450V
Rated current: 10A
Terminal Blocks: 3p screw type
Metal Part:Plated Brass/Steel Spring
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31070

Cable connector IP68

Rated operational voltage:AC250V
Rated operational Ampere(A):≤30A
Material: flame retardant/Anti UV nylon(PA66)
Crimping terminals:Nickle-plated brass
Withstand voltage(normal temperature):3KV
Operating remperature range: -40°C~+105°C
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31072

~230V | 50/60 Hz | 120° | Ra>70 | 15000h | Hg | IP 65 | RoHS COMPLIANT | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

VEGA SLIM

98VEGA10SLIM
98VEGA20SLIM
98VEGA30SLIM
98VEGA50SLIM
98VEGA100SLIM

VEGA SLIM WITH SENSOR

98VEGA10SENSLIM
98VEGA20SENSLIM
98VEGA30SENSLIM
98VEGA50SENSLIM

LED | COOL WHITE 6400K | IP65 | INDUSTRIAL

VEGA SLIM / VEGA SLIM WITH SENSOR

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98VEGA10SLIM	-	C	10	900	5500	black	66	90	18	1/50	A+ A++→A
98VEGA20SLIM	-	C	20	1800	5500	black	75	110	21	1/50	A+ A++→A
98VEGA30SLIM	**98VEGA30SLIME**	C	30	2700	5500	black	95	130	22	1/30	A+ A++→A
98VEGA50SLIM	**98VEGA50SLIME**	C	50	4500	5500	black	132	186	25	1/20	A+ A++→A
98VEGA100SLIM	**98VEGA100SLIME**	C	100	9000	5500	black	190	280	28	1/10	A+ A++→A
98VEGA10SENSLIM	-	C	10	900	5500	black	90	120	25	1/40	A+ A++→A
98VEGA20SENSLIM	-	C	20	1800	5500	black	91	121	25	1/40	A+ A++→A
98VEGA30SENSLIM	**98VEGA30SSE**	C	30	2700	5500	black	118	158	25	1/20	A+ A++→A
98VEGA50SENSLIM	**98VEGA50SSE**	C	50	4500	5500	black	145	200	26	1/10	A+ A++→A

Body: Plastic+Aluminium | **LED driver:** linear | **Light source:** SANAN | **Input voltage:** 220V-240V AC | **Cable length:** 300 mm | **Ambient Temperature:** -30°C÷ +65°C
Sensor: | **Detection Range:**110° | **Detection Distance:** MAX 8m | **Ambient Light:** 50lux | **Detection Motion Speed:** 0.6-1.5m/s;

Terminal box IP44

Material: PC
Voltage: 450V
Rated current: 6A
Wiring Capacity: 0.5-4.0mm2

Cat. Number: 31071

Terminal box IP65

Material: Polypropylene 94-V2 grade
Sunscreen Rating:Sun Protection(UV)
Voltage: 450V
Rated current: 10A
Terminal Blocks: 3p screw type
Metal Part:Plated Brass/Steel Spring
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31070

Cable connector IP68

Rated operational voltage:AC250V
Rated operational Ampere(A):≤30A
Material: flame retardant/Anti UV nylon(PA66)
Crimping terminals:Nickle-plated brass
Withstand voltage(normal temperature):3KV
Operating remperature range: -40°C~+105°C
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31072

~230V | 50/60 Hz | SMD | 110° | Ra>70 | 20000h | Hg | IP 65 | RoHS | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

VEGA SLIM

98VEGA10SLIM/WH
98VEGA20SLIM/WH
98VEGA30SLIM/WH
98VEGA50SLIM/WH
98VEGA100SLIM/WH

VEGA SLIM WITH SENSOR

98VEGA20SENSLIM/WH
98VEGA30SENSLIM/WH
98VEGA50SENSLIM/WH

LED | NEUTRAL WHITE 4000K | IP65 | INDUSTRIAL

VEGA SLIM / VEGA SLIM WITH SENSOR

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98VEGA10SLIM/WH	-	C	10	900	4000	white	66	90	18	1/50	A+ A++→A
98VEGA20SLIM/WH	-	C	20	1800	4000	white	75	110	21	1/50	A+ A++→A
98VEGA30SLIM/WH	**98VEGA30S/WHE**	C	30	2700	4000	white	95	130	22	1/30	A+ A++→A
98VEGA50SLIM/WH	**98VEGA50S/WHE**	C	50	4500	4000	white	132	186	25	1/20	A+ A++→A
98VEGA100SLIM/WH	**98VEGA100S/WHE**	C	100	9000	4000	white	190	280	28	1/10	A+ A++→A
98VEGA20SENSLIM/WH	-	C	20	1800	4000	white	91	121	25	1/40	A+ A++→A
98VEGA30SENSLIM/WH	**98VEGA30SS/WHE**	C	30	2700	4000	white	118	158	25	1/20	A+ A++→A
98VEGA50SENSLIM/WH	**98VEGA50SS/WHE**	C	50	4500	4000	white	145	200	26	1/10	A+ A++→A

Body: Plastic+Aluminium | **LED driver:** linear | **Light source:** SANAN | **Input voltage:** 220V-240V AC | **Cable length:** 300 mm | **Ambient Temperature:** -30°C÷ +65°C
Sensor: | **Detection Range:**110° | **Detection Distance:** MAX 8m | **Ambient Light:** 50lx | **Detection Motion Speed:** 0.6-1.5m/s;

Terminal box IP44

Material: PC
Voltage: 450V
Rated current: 6A
Wiring Capacity: 0.5-4.0mm2

Cat. Number: 31071

Terminal box IP65

Material: Polypropylene 94-V2 grade
Sunscreen Rating:Sun Protection(UV)
Voltage: 450V
Rated current: 10A
Terminal Blocks: 3p screw type
Metal Part:Plated Brass/Steel Spring
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31070

Cable connector IP68

Rated operational voltage:AC250V
Rated operational Ampere(A):≤30A
Material: flame retardant/Anti UV nylon(PA66)
Crimping terminals:Nickle-plated brass
Withstand voltage(normal temperature):3KV
Operating remperature range: -40°C~+105°C
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31072

~230V | 50/60 Hz | SMD | 110° | Ra>70 | 20000h | IP 65 | RoHS | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

VEGA SLIM

98VEGA150SLIM
98VEGA200SLIM

LED | COOL WHITE 6400K | IP65 | INDUSTRIAL

VEGA SLIM

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98VEGA150SLIM	C	150	13500	5500	black	226	315	35	1/1	A+ A+→A
98VEGA200SLIM	C	200	18500	5500	black	320	400	85	1/1	A+ A+→A

Body: Plastic+Aluminium | **LED driver:** linear | **Light source:** SANAN | **Input voltage:** 220V-240V AC | **Cable length:** 300 mm | **Ambient Temperature:** -30°C÷ +65°C

Terminal box IP44

Material: PC
Voltage: 450V
Rated current: 6A
Wiring Capacity: 0.5-4.0mm2

Cat. Number: 31071

Terminal box IP65

Material: Polypropylene 94-V2 grade
Sunscreen Rating:Sun Protection(UV)
Voltage: 450V
Rated current: 10A
Terminal Blocks: 3p screw type
Metal Part:Plated Brass/Steel Spring
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31070

Cable connector IP68

Rated operational voltage:AC250V
Rated operational Ampere(A):≤30A
Material: flame retardant/Anti UV nylon(PA66)
Crimping terminals:Nickle-plated brass
Withstand voltage(normal temperature):3KV
Operating remperature range: -40°C~+105°C
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31072

~230V | 50/60 Hz | SMD | 110° | Ra>70 | 20000h | Hg | IP 65 | RoHS | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LYRA RGB
98LYRA15RGB

LYRA RGB
98LYRA50RGB

LYRA RGB
98LYRA30RGB

LED IP65 INDUSTRIAL

LYRA RGB

Catalogue number	Product category	Model	Watt (W)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98LYRA15RGB	C	LYRA15	15	RGB	black	140	195	50	1/20	A++→A
98LYRA30RGB	C	LYRA30	30	RGB	black	184	254	57	1/10	A++→A
98LYRA50RGB	C	LYRA50	50	RGB	black	233	300	67	1/5	A++→A

Body: Aluminium casting | **LED driver:** mounted in the body | **Light source:** Epistar SMD2835 | **Input voltage:** 200-240V | **Remote-controlled distance:** 6-8M
Ambient Temperature: - 30°C÷ +55°C | **Diffuser:** Tempered glass

Terminal box IP44

Material: PC
Voltage: 450V
Rated current: 6A
Wiring Capacity: 0.5-4.0mm2

Cat. Number: 31071

Terminal box IP65

Material: Polypropylene 94-V2 grade
Sunscreen Rating:Sun Protection(UV)
Voltage: 450V
Rated current: 10A
Terminal Blocks: 3p screw type
Metal Part:Plated Brass/Steel Spring
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31070

Cable connector IP68

Rated operational voltage:AC250V
Rated operational Ampere(A):≤30A
Material: flame retardant/Anti UV nylon(PA66)
Crimping terminals:Nickle-plated brass
Withstand voltage(normal temperature):3KV
Operating remperature range: -40°C~+105°C
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31072

~230V | 50/60 Hz | 120° | Ra>70 | 20000h | Hg | IP 65 | RoHS COMPLIANT | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

STADIUM FLOOD LIGHTS PHOENIX
98PHOENIX720CW/BL

STADIUM FLOOD LIGHTS PHOENIX
98PHOENIX960CW/BL

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | IP67 | INDUSTRIAL

STADIUM FLOOD LIGHTS PHOENIX

Catalogue number	Product category	Watt (W)	Lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98PHOENIX720CW/BL	C	720	86400	5500K	30°	833,4	442	201	1/1	A++→A
98PHOENIX960CW/BL	C	960	115200	5500K	30°	1090	442	201	1/1	A++→A



Body: Aluminium | **LED driver:** MEANWELL| **Light source:** PHILIPS | **Input voltage:** 230V AC | **Ambient Temperature:** -20°C÷ +65°C

~230V | 50000h | >20000 | Hg | IP 67 | RoHS | EMC | CE | 5+0 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

STADIUM FLOOD LIGHTS PHOENIX
98PHOENIX240CW/BL

STADIUM FLOOD LIGHTS PHOENIX
98PHOENIX480CW/BL

STADIUM FLOOD LIGHTS PHOENIX
98PHOENIX360CW/BL

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | IP67 | INDUSTRIAL

STADIUM FLOOD LIGHTS PHOENIX

Catalogue number	Product category	Watt (W)	Lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98PHOENIX240CW/BL	C	240	28800	5500K	30°	435,4	341	190	1/1	A++→A
98PHOENIX360CW/BL	C	360	43200	5500K	30°	618,4	341	200	1/1	A++→A
98PHOENIX480CW/BL	C	480	57600	5500K	30°	579,4	442	201	1/1	A++→A

Body: Aluminium | **LED driver:** MEANWELL| **Light source:** PHILIPS | **Input voltage:** 230V AC | **Ambient Temperature:** -20°C÷ +65°C

~230V | 50000h | >20000 | Hg | IP 67 | RoHS | EMC | F | CE | 5+0 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED | COOL WHITE 6400K | IP65 | 110° | INDUSTRIAL

UNTIL SUPPLY LAST

SIRIUS SMD

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98SIRIUS50SMD	F	SIRIUS50SMD	50	5000	6500	black	137	35	170	1/10	A++→A
98SIRIUS150SMD	F	SIRIUS150SMD	150	15000	5500	black	310	80	430	1/10	A++→A
98SIRIUS200SMD	F	SIRIUS200SMD	200	20000	5500	black	386	106	560	1/10	A++→A
98SIRIUS250SMD	F	SIRIUS250SMD	250	25000	5500	black	386	106	560	1/10	A++→A





Body: Aluminium | **LED driver:** mounted in the body | **Light source:** 2835SMT Epistar | **Input voltage:** 100V-240V AC | **Ambient Temperature:** -30°C÷ +65°C

Material: PC
Voltage: 450V
Rated current: 6A
Wiring Capacity: 0.5-4.0mm2

Cat. Number: 31071

Terminal box IP44

Material: Polypropylene 94-V2 grade
Sunscreen Rating:Sun Protection(UV)
Voltage: 450V
Rated current: 10A
Terminal Blocks: 3p screw type
Metal Part:Plated Brass/Steel Spring
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31070

Terminal box IP65

Rated operational voltage:AC250V
Rated operational Ampere(A):≤30A
Material: flame retardant/Anti UV nylon(PA66)
Crimping terminals:Nickle-plated brass
Withstand voltage(normal temperature):3KV
Operating remperature range: -40°C~+105°C
Wiring Capacity: 0.5-2.5mm2

Cat. Number: 31072

Cable connector IP68

~230V | 50/60 Hz | SMD | 110° | Ra>70 | 30000h | IP 65 | RoHS | F | CE | 5+0 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

RECHARGEABLE WORKLAMP SMD

98FLOOD10Y

UNTIL SUPPLY LAST

LED NEUTRAL WHITE 4000K **IP44**

RECHARGEABLE WORKLAMP SMD

Catalogue number	Product category	Model	Watt (W)	Whole lamp lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98FLOOD10Y	F	FLOOD10Y	10	600	4000	yellow	242	25	215	1/10	A++→A

Body: Aluminium | **Light source:** SMD2835| **Input voltage:** 100V-240V | All-round rotation 360° | Any angle hover | With adaptor and car charge
Time of battery work: 100% light-2h; 50% light-4h

~230V | 50/60 Hz | 110° | 20000h | IP 44 | RoHS COMPLIANT | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

LED WORK FLOODLIGHTS

98FLOOD30S
98FLOOD50S

LED | IP65 | 220V

LED WORK FLOODLIGHTS

Catalogue number	Product category	Model	Watt (W)	Whole lamp lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
98FLOOD30S	C	FLOOD30S	30	2700	5500	110°	163.5	210	30.5	1/20	A++→A
98FLOOD50S	C	FLOOD50S	50	4500	5500	110°	171	227	32	1/20	A++→A

Material: Aluminium | **Color body:** Yellow | **Working Temperature:** -20°C +45°C |Two meters 3*1.0mm2 rubber cable with plug

~230V | 50/60 Hz | 110° | 20000h | RoHS | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ATLAS 45
98ATLAS45/BL2

ATLAS Sim
98ATLASSIM/1
98ATLASSIM/2

ATLAS Ring
98ATR107
98ATLASRING/1
98ATLASRING/2

IP65 INDUSTRIAL

UNTIL SUPPLY LAST

ATLAS

Catalogue number	Product category	Watt (W)	Lampholder	Colour	Length1 (mm)	Length2 (mm)	Width (mm)	Width2 (mm)	Height (mm)	Current (A)	Control gear	Packing/Box (pcs)	Energy class
98ATLAS45/BL1	F	70	Rx7s	black	435	350	232	-	85	-	empty fixture	1/4	A++→C
98ATLAS45/W1	F	70	Rx7s	white	435	350	232	-	85	-	empty fixture	1/4	A++→C
98ATLASSIM/1	F	70	Rx7s	black	232	210	280	220	170	-	empty fixture	1/6	A++→C
98ATLASSIM/2	F	150	Rx7s	black	232	210	280	220	170	-	empty fixture	1/6	A++→C
98ATR107	F	70	Rx7s	black	325	280	230	210	93	0,95	magnetic	1/6	A++→C
98ATLASRING/1	F	70	Rx7s	black	325	280	230	210	93	-	empty fixture	1/6	A++→C
98ATLASRING/2	F	150	Rx7s	black	325	280	230	210	93	-	empty fixture	1/6	A++→C







Body: aluminium | **Diffuser:** tempered glass | **Control gear:** mounted in the body
Ambient Temperature: -20°C ÷ +65°C

~230V | 50/60 Hz | MH-7 | Rx7s | 2,5mm² | IP 65 | RoHS | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

VEGA IP44
989009LED
989012LED
989008LED

VEGA WITH SENSOR IP44
989019LED

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | IP44 | IP65

UNTIL SUPPLY LAST

VEGA

Catalogue number	Product category	Model	Watt (W)	Lamp	Whole fixture lumens (lm)	Colour temp. (K)	Socket	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
989009LED	F	VEGAJ-78	5.5	LED	440	4000	R7s	grey	200	145	120	1/20	A+ A++→A
989012LED	F	VEGA J-118	7.5	LED	700	4000	R7s	grey	260	210	230	1/10	A+ A++→A
989008LED	F	VEGAJ-78	5.5	LED	440	4000	R7s	black	200	145	120	1/20	A+ A++→A
989019LED	F	VEGA J-118 with sensor	7.5	LED	700	4000	R7s	white	260	210	230	1/10	A+ A++→A
989020LED	F	VEGA J-118 with sensor	7.5	LED	700	4000	R7s	black	260	210	230	1/10	A+ A++→A

Body: aluminium casting | **Ambient Temperature:** -30°C÷ +65°C | **Diffuser:** Tempered glass

~230V | 50/60 Hz | 120° | Ra>70 | 20000h | Hg | IP 65 | IP 44 | RoHS | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

BERLIN LED SMD

98BERLIN100SMD
98BERLIN150SMD
98BERLIN200SMD

LED | COOL WHITE 6400K | IP65 | INDUSTRIAL

BERLIN LED SMD, HIGH LUMEN STREET LIGHT

Catalogue number	Product category	Watt (W)	LED chip lumens (lm)	Colour temp (K)	Beam angle	Colour body	Diameter of the pole (mm)	Length (mm)	Width (mm)	Height (mm)	Packing/ Box (pcs)	Energy class
98BERLIN100SMD	C	100	15000	5500	70x145 °	Grey	60	611	89	240	1	A++→A
98BERLIN150SMD	C	150	22500	5500	70x145 °	Grey	60	680	89	260	1	A++→A
98BERLIN200SMD	C	200	30000	5500	70x145 °	Grey	60	680	89	260	1	A++→A

WALL MOUNTING ACCESSORIES
Diam.: 60mm
Suitable: for road fixtures Berlin from 100W to 200W
Catalogue number: 98POLE60

POLE MOUNTING ACCESSORIES
Diam.: 60mm
Suitable: for road fixtures Berlin from 100W to 200W
Catalogue number: 98POLE60P

Body: Alu+PC cover | **Input voltage:** 100V-240V AC | PF>0,9

~230V | 50/60 Hz | SMD | 90° | Ra>80 | 35000h | Hg | IP 65 | RoHS COMPLIANT | F | CE | 5+0 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MADRID SMD

98MADRID30SMD

LED | COOL WHITE 6400K | IP65 | INDUSTRIAL

MADRID SMD, LED CHIP PHILIPS

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	LED chip lumens (lm)	Colour temp (K)	Beam angle	Colour body	Diameter of the pole (mm)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98MADRID30SMD	**98MADRID30SMDE**	C	30	3600	5500	90°	Grey	38	362	54	143	1/10	A++→A
98MADRID50SMD	**98MADRID50SMDE**	C	50	6000	5500	90°	Grey	60	476	74	194	1/5	A++→A
98MADRID100SMD	**98MADRID100SMDE**	C	100	12000	5500	90°	Grey	60	567	87	233	1/4	A++→A
98MADRID150SMD	-	C	150	18000	5500	90°	Grey	60	673	101	395	1/4	A++→A
98MADRID200SMD	-	C	200	24000	5500	90°	Grey	60	742	114	337	1/2	A++→A
98MADRID250SMD	-	C	250	28800	5500	90°	Grey	60	742	114	337	1/2	A++→A

WALL MOUNTING ACCESSORIES
Diam.: 38mm
Suitable: for 98MADRID30SMD
Catalogue number: 98POLE38
Diam.: 60mm
Suitable: for road fixtures Madrid from 50W to 250W
Catalogue number: 98POLE60

POLE MOUNTING ACCESSORIES
Diam.: 38mm
Suitable: for 98MADRID30SMD
Catalogue number: 98POLE38P
Diam.: 60mm
Suitable: for road fixtures Madrid from 50W to 250W
Catalogue number: 98POLE60P

Body: Alu+PC cover | **LED driver:** Isolated driver | **Light source:** Philips | **Input voltage:** 180V-265V AC | **Ambient temperature:** -25°C÷ +45°

~230V | 50/60 Hz | SMD | 90° | Ra>80 | 35000h | IP 65 | RoHS | F | CE | 5+0 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

STREET 300 SMD

98STREET300SMD

LED | COOL WHITE 6400K | IP65 | DIMMABLE | INDUSTRIAL

UNTIL SUPPLY LAST

STREET SMD, LED CHIP SAMSUNG

Catalogue number	Product category	Dimmable	Watt (W)	LED chip lumens (lm)	Colour temp (K)	Beam angle	Colour body	Diameter of the pole (mm)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98STREET150SMD	F*	-	150	18000	5500	85°x135°	Silver aluminium	60	501	290	87	1/1	A++→A
98STREET200SMD	F*	-	200	24000	5500	85°x135°	Silver aluminium	60	582	290	87	1/1	A++→A
98STREET300SMD	F*	Yes	300	36000	5500	85°x135°	Silver aluminium	60	796	347	142	1/1	A++→A





WALL MOUNTING ACCESSORIES
Diam.: 60mm
Colour body: grey
Size (mm): Diameter 60 / Width 150 / Height 250
Catalogue number: 98POLE60
Packing (pcs): 1

POLE MOUNTING ACCESSORIES
Diam.: 60mm
Colour body: grey
Size (mm): Diameter 60 / Width 150 / Height 250
Catalogue number: 98POLE60P
Packing (pcs): 1

Body: Silver aluminium | **LED driver:** mounted in the body | **Light source:** Samsung 3030SMD | **Input voltage:** 100V-240V AC | **Ambient temperature:** -30°C÷ +65°C

*Until supply last

~230V | 50/60 Hz | SMD | 135° | Ra>80 | 30000h | Hg | IP 65 | RoHS | F | CE | 5+2 standard +extended | 7 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ROUTE SMD STELLAR

98ROUTE30SMD
98ROUTE50SMD
98ROUTE100SMD
98ROUTE150SMD

LED COOL WHITE 6400K **IP65**

ROUTE SMD STELLAR

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp (K)	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98ROUTE30SMD	**98ROUTE30SMDE**	C	30	3000	5000-5500	90°	130	57	316	1/20	A++→A
98ROUTE50SMD	**98ROUTE50SMDE**	C	50	5000	5000-5500	90°	155	57	355	1/10	A++→A
98ROUTE100SMD	**98ROUTE100SMDE**	C	100	10000	5000-5500	90°	160	67	420	1/10	A++→A
98ROUTE150SMD	-	C	150	15000	5000-5500	90°	170	67	546	1/5	A++→A

Ultra thin design

WALL MOUNTING ACCESSORIES
Diam.: 45mm
Suitable: for 98ROUTE30SMD, 98ROUTE50SMD and 98ROUTE100SMD
Catalogue number: 98POLE45
Diam.: 60mm
Suitable: 98ROUTE150SMD
Catalogue number: 98POLE60

POLE MOUNTING ACCESSORIES
Diam.: 45mm
Suitable: for 98ROUTE30SMD, 98ROUTE50SMD and 98ROUTE100SMD
Catalogue number: 98POLE45P
Diam.: 60mm
Suitable: for 98ROUTE150SMD
Catalogue number: 98POLE60P

Body: Aluminium | **Cover:** PC | **Voltage:** 100-265 VAC | **Light source:** Focus | **Ambient temperature:** -35°C÷ +45°C

~230V | 50/60 Hz | Ra>80 | 20000h | Hg | RoHS | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

AVENUE 100 SMD
98AVENUE100SMD

AVENUE 50 SMD
98AVENUE50SMD

AVENUE 30 SMD
98AVENUE30SMD

LED COOL WHITE 6400K **IP67**

UNTIL SUPPLY LAST

AVENUE SMD, LED CHIP PHILIPS

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp (K)	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98AVENUE30SMD	F	30	3000	5500	70°x150°	365	18	90	1/1	A++→A
98AVENUE50SMD	F	50	5000	5500	70°x150°	420	15	234	1/1	A++→A
98AVENUE100SMD	F	100	10000	5500	120°x65°	605	15	295	1/1	A++→A

Ultra thin design

WALL MOUNTING ACCESSORIES
Diam.: 60mm
Colour body: grey
Size (mm): Diameter 60 / Width 150 / Height 250
Catalogue number: 98POLE60
Packing (pcs): 1

POLE MOUNTING ACCESSORIES
Diam.: 60mm
Colour body: grey
Size (mm): Diameter 60 / Width 150 / Height 250
Catalogue number: 98POLE60P
Packing (pcs): 1

Body: Aluminium casting | **LED driver:** mounted in the body | **Light source:** SMD3030 | **Input voltage:** 220-240V | **Working temperature:** -25+55°C

~230V | 50/60 Hz | Ra>80 | 35000h | Hg | IP 67 | RoHS | EMC | F | CE | 5+0 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR LED STREET LIGHTS WITH SENSOR
98SOL103

SOLAR LED STREET LIGHTS WITH SENSOR
98SOL104

SOLAR LED STREET LIGHTS WITH SENSOR
98SOL106

SOLAR LED STREET LIGHTS WITH SENSOR
98SOL105

LED COOL WHITE 6400K **IP65** **Solar**

SOLAR LED STREET LIGHTS WITH SENSOR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Solar panel (Wp)	Battery (V/mAh)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
98SOL103	C	30	360	6800-7200	5V/7W	3.2V/5000mAh	207	384	57	1/10	A++→A
98SOL104	C	60	720	6800-7200	5V/11W	3.2V/10000mAh	235	479	57	1/5	A++→A
98SOL105	C	90	1080	6800-7200	5V/14W	3.2V/15000mAh	256	618	57	1/5	A++→A
98SOL106	C	120	1440	6800-7200	5V/18W	3.2V/20000mAh	256	720	57	1/5	A++→A

WALL MOUNTING ACCESSORIES
Diam.: 45mm
Catalogue number: 98POLE45

POLE MOUNTING ACCESSORIES
Diam.: 45mm
Catalogue number: 98POLE45P

SMD 120° RoHS COMPLIANT 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SOLAR LED STREET LIGHTS WITH SENSOR

98SOL100
98SOL101
98SOL102

LED | COOL WHITE 6400K | IP65 | Solar

UNTIL SUPPLY LAST

SOLAR LED STREET LIGHTS WITH SENSOR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Solar panel (Wp)	Battery (V/mAh)	Sensor range (m)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
98SOL100	F	20	400	6000	2.3	3.7V/2400mAh	2-6	137	224.4	41.5	1/1	A++→A
98SOL101	F	40	850	6000	7	3.7V/6000mAh	3-8	193.7	351.4	50.8	1/1	A++→A
98SOL102	F	80	1600	6000	9.5	7.4V/5400mAh	3-8	232	413	58	1/1	A++→A

Material: ABS + PC, anti UV and glossy, V0 fireproof | **Colour body:** Black | **Detection angle:** 120° | **Beam angle:** 140°x 70° | **Installation height 98SOL100:** 2-4meters, other models: 3-5m | Posibility to mounting on Wall or Lamp-post | **First 5 hours lighting:** Full brightness+ Weak brightness | After 5 hours or battery capacity<30%: Full brightness+ Weak brightnes+ OFF | **Solar panels:** Poly-cristalline silicone; Frosted surface- scratch resistant | **LED&Lens:** LM-80 LEDs 2835SMD; high transmittance PC optical lens | Accessory for wall mounted installation: included

Accessory for wall mounted installation

SMD | Ra>80 | Hg | RoHS COMPLIANT | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

DUBLIN SMD STELLAR

98DUBLIN100SMD
98DUBLIN150SMD
98DUBLIN200SMD

LED | COOL WHITE 6400K | **IP65**

DUBLIN SMD STELLAR

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98DUBLIN100SMD	**98DUBLIN100SMDE**	C	100	10000	5500	100°	Grey	237	90	1/10	A++→A
98DUBLIN150SMD	-	C	150	15000	5500	100°	Grey	302	96	1/5	A++→A
98DUBLIN200SMD	-	C	200	20000	5500	100°	Grey	360	96	1/5	A++→A

Gear box: Alu+Glass | **LED driver:** Linear | **Light source:** Sanan | **Input voltage:** 220V-240V AC | **Ambient temperature:** -25°C÷ +45°C

~230V | 50/60 Hz | Ra>80 | 20000h | Hg | IP 65 | RoHS COMPLIANT | EMC | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FESTA SMD STELLAR

98FESTA150SMD
98FESTA200SMD

LED | COOL WHITE 6400K | **IP65**

UNTIL SUPPLY LAST

FESTA SMD STELLAR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98FESTA150SMD	F	150	15000	5000-5500	120°	black	320	159	1/1	A++→A
98FESTA200SMD	F	200	20000	5000-5500	120°	black	380	166	1/1	A++→A



Gear box: Aluminium + Graphene | **Cover:** PC | **Voltage:** 180-265 VAC | **Light source:** Sanan| **Ambient temperature:** -25°C÷ +45°C

~230V | 50/60 Hz | Ra>80 | 25000h | Hg | IP 65 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

VIENA SMD

98VIENA100SMD
98VIENA150SMD
98VIENA200SMD
98VIENA250SMD

LED | COOL WHITE 6400K | **IP65**

VIENA SMD

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98VIENA100SMD	**98VIENA100SMDE**	C	100	13000	5500	90°	Black	290	140	1/1	A++→A
98VIENA150SMD	-	C	150	19500	5500	90°	Black	350	140	1/1	A++→A
98VIENA200SMD	-	C	200	26000	5500	90°	Black	400	140	1/1	A++→A
98VIENA250SMD	-	C	250	31200	5500	90°	Black	400	140	1/1	A++→A

Gear box: Alu+PC | **LED driver:** Isolated | **Input voltage:** 180-265 VAC | **Light source:** Sanan| **Ambient temperature:** -25°C÷ +45°C

~230V | 50/60 Hz | Ra>80 | 35000h | Hg | IP 65 | RoHS COMPLIANT | EMC | F | CE | 5+0 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

VECA SMD
98VECA150SMD

VECA SMD
98VECA120SMD

VECA SMD
98VECA200SMD
(98VECA200SMDDGR)
98VECA250SMD
(98VECA250SMDDGR)

LED COOL WHITE 6400K **IP65**

UNTIL SUPPLY LAST

VECA SMD, LED CHIP PHILIPS

Catalogue number	Variant	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
98VECA120SMD		F	120	12000	5500	120°	grey	400	120.3	1/1	A++→A
98VECA150SMD		F	150	15000	5500	120°	grey	382	60	1/1	A++→A
98VECA200SMD	DGR	F	200	20000	5500	120°	black	460	170.3	1/1	A++→A
98VECA250SMD	DGR	F	250	25000	5500	120°	black	500	180	1/1	A++→A

Gear box: Aluminium | **LED driver:** mounted in the gear box | **Light source:** Philips | **Ambient temperature:** -25°C÷ +55°C

~230V 50/60 Hz Ra>80 25000h IP 65 RoHS EMC F CE 5+0 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MINICOLOR
98MINICOL-BL

MINICOLOR
98MINICOL-WT

MINICOLOR
98MINICOL-R

MINICOLOR
98MINICOL-G

MINICOLOR
98MINICOL-B

LED | COOL WHITE 6400K | **IP20**

UNTIL SUPPLY LAST

MINICOLOR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Diameter1 (mm)	Height (mm)	Height1 (mm)	Packing/Box (pcs)	Energy class
98MINICOL-BL	F	30	2400	5500	black	220	115	280	120	1/1	A++→A
98MINICOL-WT	F	30	2400	5500	white	220	115	280	120	1/1	A++→A
98MINICOL-R	F	30	2400	5500	red	220	115	280	120	1/1	A++→A
98MINICOL-G	F	30	2400	5500	green	220	115	280	120	1/1	A++→A
98MINICOL-B	F	30	2400	5500	blue	220	115	280	120	1/1	A++→A



Reflector: aluminium | **Gear box:** aluminium casting | **LED driver:** mounted in the gear box | **Light source:** Epistar | **Ambient Temperature:** - 30°C÷ +65°C

~230V | 50/60 Hz | COB | 90° | Ra>80 | 30000h | Hg | IP 20 | RoHS | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY